



Rotary 2-post lift "SPO-Serie"

"SPOA40AV-EH2", incl. 2nd Operating Unit "CONTROL - SPOA3TC-NC" and 8-piece set of adapter extensions "VSG.2CHYD.902917", load capacity: 4000 kg, total height: 4170 mm, superstructure: asymmetrical, operation: electric

Technical data:

Lifting height: 1950 mm

Lifting time: 30 s

Column spacing: 2829 mm

Drive-through width: 2546 mm

Total width: 3211 mm

Drive power: 4.0 kW

Drive voltage: 400 V / 50 Hz

Total height EH 2: 4230 mm

Cut-off height EH 2: 4065 mm

Support arm length front min. / max.: 470 / 1039 mm (3-fold)

Support arm length hi. min. / max.: 723 / 1478 mm (3-fold)

Turntable height min. / max.: 86 / 115 mm

Price: €3,349.95

Basic Data

Supplier Article Number:	SPOA40AV-EH2
EAN	4057612975666
MSRP:	€8,157.45
SB-Article	No
Brand/Supplier	Rotary
Unit of measure:	PIECE

Technical Data

Design	lift
Drive	electrohydraulic
Drive power	4.0 kW
Drive voltage	400.0 V

Features	without base frame
Height	417.0 cm
Load	4000.0 kg
Main colour	silver
Max. lifting	195.0 cm
Type	2-post lift
Variant	Article
Width	349.6 cm

More product images

