

VICTORIA Electric trekking bike "eManufaktur 12.9" Mod. 22

wave, 28", aqua blue matt, 1x11-speed SHIMANO "Deore XT", 54 cm / L

RRP: €3,399.95

Top touring e-bike with modern navigationThe "eManufaktur 12.9" is the top model with derailleur. The sporty BOSCH "Performance CX" motor in combination with the long range BOSCH "PowerTube 625" battery make up a large part of the premium equipment. The e-bike gets a fresh coat of paint with the new two-tone design and the reduced VICTORIA brand logo. Also new is the "Kiox" color display, on which routes and bike data can be read. It also ensures navigation through unknown territory. The proven sporty SHIMANO 11-speed "Deore XT" derailleur shines in the latest Linkglide technology, which allows the already precise shifting even crisper. Signs of wear also become noticeable more slowly.The drive is supported by the sporty BOSCH "Performance CX" mid-motor, which ensures a smooth, balanced ride thanks to its low center of gravity. With 85 Nm of torque, it propels you forward at up to 25 km/h. Even hilly terrain is no challenge for it. Even mountainous terrain is no challenge for it. The SUNTOUR suspension fork and the wide SCHWALBE tires ensure high touring comfort.The lighting makes the "eManufaktur 12.9" fit for city traffic. The CONTEC LED front light illuminates the way through the darkness as bright as day with a 120 lux. The rear light is equipped with a stoplight function, through which following cyclists or even motorists get a chance to react better to braking maneuvers. On the RACKTIME carrier can be quickly and easily attached all common panniers with click mechanism.

Basic Data

Supplier Article Number:	BK22HV0550
EAN	4251507984447
MSRP:	€3,399.95
WEEE registration number	DE92509320
DST-Code	1B01
SB-Article	No
Bidex-Code	122010
Fedas-Code	155021
Brand/Supplier	VICTORIA
Unit of measure:	PIECE
Weight	27.7 kg

Technical Data

Battery capacity	625.0 Wh
Bosch Smart System	no
Brake system	hydraulic disc brake
Colour designation	aqua blue matt

Drive	chain
Drive system	BOSCH Performance Line CX
Drive version	middle motor
E-bike	yes
Engine power	250 W
Features	chain guard , electronic sliding aid , fender , frame lock , suspension fork
Frame height	54 cm
Frame shape	wave
Frame size	L
Gears	11-speed
Gender	ladies
Main colour	green
Material	aluminium
Model range	eManufaktur
Permissible system weight	149 kg
Secondary colour	black
Shifting name	1x11-Gang SHIMANO "Deore XT"
Shifting type	derailleur shifting
Support	up to 25km/h
Transmission	1x 11-speed
Travel	80 mm
Type	trekking bike
Wheel size	28 "

Specifications

Battery	BOSCH "Powertube 625", Lithium-Ionen mit BMS, 625 Wh
Bottom bracket	BOSCH
Brake	TEKTRO "HD-T390"
Brake lever	TEKTRO "HD-T390"
Chain / belt	SHIMANO "CN-LG500"
Chain guard	HESLING "Velo" Bosch Gen.4 schwarz matt
Chain ring / pulley	LASCO, 42 Z., Narrow Wide
Charger	BOSCH 4 Ah
Crank	FSA "CK-745", Gen.4
Derailleur hanger	Slider Dropout
Display	BOSCH, "Kiox" 4-Stufen, Remote Control, Schiebehilfe
Engine	BOSCH Mittelmotor Gen.4 "Performance CX", 36 V, 250 W
Fender	CURANA "Apollo", 60mm, schwarz matt, Spoiler
Fork	RST "Aerial 29-15", einstellbar, Lockout, 80mm,Disc, Tapered
Frame	Bosch-Intube-Frame, Aluminium 6061
Frame Lock	CONTEC "Powerloc" M
Front hub	SHIMANO "HB-MT400", QR 15, Disc, Center Lock

Front light	CONTEC "Dlux 120 E+" 120 Lux
Front rotor	TEKTRO "TR180-45", 180mm, Center-Lock
Front tire	CONTINENTAL "Contact Plus" 50-622
Grips	CONTEC "Tour Wing"
Handlebar	ERGOTEC "Riser Bar 50", 720 mm, Ø31,8 mm, schwarz
Pedals	UNION "SP-828", Alu, Antislip
Rear carrier	MIK-ALU-GEPÄCKTRÄGER MIK-System
Rear derailleur	SHIMANO "Deore XT RD-M8130-SGS", 11-fach
Rear hub	SHIMANO "Deore FH-UR600", Disc
Rear light	CONTEC „TL-335 E-Stop“, mit Stoplicht
Rear rotor	TEKTRO "TR180-45", 160mm, Center-Lock
Rear tire	CONTINENTAL "Contact Plus" 50-622
Rims	MACH "630 KARMA Disc"
Saddle	SELLE ROYAL "Orbis" Relax
Seatpost	ERGOTEC Patent "Skalar", Ø 31,6 mm, 15mm Setback, Alu, black
Sensor	Pedal pressure measuring im Motor + speed sensor
Shifting lever	SHIMANO "Deore XT SL-M8130-R10"
Spokes	2,0 mm, Niro, black
Sprocket / pulley	SHIMANO "CS-LG600-11" 11-50 Z.
Stands	URSUS "King2", Hinterbau, 40 mm, verstellbar
Stem	ERGOTEC "Octopus XL Ahead 50", Ø31,8 mm, 115mm, verstellbar, schwarz