



BS-BATTERY Battery "BB4L-B"

Standard, incl. acid pack

Standard batteries are pre-charged dry. Before commissioning, fill the battery with battery acids and leave it open for approx. 1-2 hours, then attach the bleed hose and connect the battery.

Attention: Batteries from 12 V may require recharging!

RRP €19.77

Basic Data

| | |
|--------------------------|---------------|
| Supplier Article Number: | 310590 |
| EAN | 3661451003384 |
| MSRP: | €19.77 |
| SB-Article | No |
| Brand/Supplier | BS-BATTERY |
| Unit of measure: | PIECE |
| Weight | 1.55 kg |

Technical Data

| | |
|------------------------|---------------------------|
| Bleeding | right central |
| Capacity 10 Hr | 4.0 Ah |
| Capacity 20 Hr | 4.2 Ah |
| Cold start current CCA | 50 A |
| Comparison number | BB4L-B |
| Design | standard , with acid pack |
| Energy | 51.20 Wh |
| Filling quantity | 0.3 l |
| Height | 92.0 mm |
| Length | 120.0 mm |
| Minus pole | front left |
| Plus pole | front right |
| Range of application | motorcycle |
| Screwing | M5 |

| | |
|----------------|---------|
| Variant | Article |
| Voltage | 12V |
| Width | 70.0 mm |