



EXIDE Battery "G12-30"

gelsealed

Solves the problem of possible leaks in a conventional battery. The electrolyte (acid) consists entirely of a non-liquid gel. Even in the event of damage to the Housing of the Battery, this electrolyte cannot leak. It provides the ultimate protection against possible acid damage to the motorcycle or Wheels. The service life of a gel battery is approx. 50 % longer than that of a conventional maintenance-free battery. According to the JB/4282-92 standard, a normal maintenance-free battery has a maximum service life of 200 charging cycles. This compares with up to 500 charging cycles for a gel battery.

Attention: Recharging only with so-called "intelligent charging devices" such as Optimate 4 and Intellicharger II. Damage caused by incorrect charging is not covered by the warranty!

Caution: Never open or drill into these sealed (gel) batteries or remove the sealing strip!

RRP €205.12

Basic Data

Supplier Article Number:	EXIDE GEL G30
EAN	3661024034081
MSRP:	€205.12
SB-Article	No
Brand/Supplier	EXIDE
Unit of measure:	PIECE
Weight	11.025 kg

Technical Data

Bleeding	without
Capacity 10 Hr	27.9 Ah
Capacity 20 Hr	30.0 Ah
Cold start current CCA	180 A
Design	MTF , ready-to-use
Energy	324.00 Wh
Height	186.0 mm
Length	197.0 mm

Minus pole	front right
Plus pole	front left
Range of application	motorcycle
Screwing	M6
Variant	Article
Voltage	12V
Width	132.0 mm