

YUASA Battery "YTZ6V"

MTF, maintenance-free

After removing the adhesive strip, attach the included acid pack and allow the acid to flow evenly into all cells. Let it sit for about 1–2 hours, then press the sealing strip firmly into place. Once filled, the Battery is sealed and requires no further maintenance.

Caution: Batteries rated at 12 V or higher may need to be recharged! Never open, drill into, or remove the sealing strip from these sealed (MTF) batteries!

RRP: €75.00

Basic Data

Supplier Article Number:	YTZ6V-CP
EAN	5050694015854
MSRP:	€75.00
SB-Article	No
Brand/Supplier	YUASA
Unit of measure:	PIECE
Weight	2.013 kg

Technical Data

Article type	Battery
Bleeding	internal
Capacity 10 Hr	5.0 Ah
Capacity 20 Hr	5.3 Ah
Cold start current CCA	90 A
Comparison number	BTZ6S-BS, SLA, GTZ6V, YTZ6V, Yam-52B-H2100-00
Design	MTF , with acid pack
Filling quantity	0.3 l
Height	105.0 mm
Length	113.0 mm
Minus pole	front left
Plus pole	front right
Range of application	motorcycle
Screwing	M5
Variant	Article
Voltage	12V
Width	70.0 mm