



## CONWAY MTB full suspension "RLC FS 6.9" Mod. 23

full suspension, 29", bronze metallic matt / black metallic, 12-speed SHIMANO "XT", 51 cm / L

**Price: €2,058.95**

The "RLC FS 6.9" comes up with more travel - and thus qualifies as a true marathon and downcountry bike. All bumps and uneven surfaces that come in front of the CONWAY "RLC FS 6.9" on cross-country or marathon trails are smoothed out with 120mm. To ensure full power transmission, the full-carbon race full suspension is light and laterally stiff. Your drive is provided by the SHIMANO "Deore XT Shadow Plus" shifting system with its 12 gears. From the same family come the hydraulic disc brakes. The lug tread of the tire combination of SCHWALBE, front "Racing Ray" and rear "Racing Ralph" in Evo quality, 60mm width with Addix Compound, gives you enough grip on loose ground. The DT SWISS "X 1900 Spline" wheels contribute to the lateral stiffness and plenty of drive power. The genes of the race full suspension bike come from the CONWAY siblings "WME" and "RLC", its handling is correspondingly sporty, the seating position nevertheless suitable for long distances. The "RLC FS" series is also prepared for the FOX "Livevalve" suspension systems.

### Basic Data

Supplier Article Number:	BK23HA0270
EAN	4251971103207
MSRP:	€3,499.95
Bidex-Code	101020
DST-Code	1E00
Fedas-Code	154040
SB-Article	No
Brand/Supplier	CONWAY
Unit of measure:	PIECE
Weight	12.2 kg

### Technical Data

Brake system	hydraulic disc brake
Chainstay	445 mm
Colour designation	bronze metallic matt / black metallic
Drive	chain
E-bike	no
Features	damper , suspension fork
Frame height	51 cm
Frame shape	full suspension

Frame size	L
Frame travel	100 mm
Gears	12-speed
Gender	gents
Main colour	gold
Material 1	carbon
Model series	RLC
Permissible system weight	130 kg
Reach	473 mm
Seat angle	72.0 °
Seat tube	505 mm
Secondary colour	black
Shifting name	12-Gang SHIMANO "XT"
Shifting type	derailleur shifting
Stack	604 mm
Steering tube	115 mm
Steering tube angle	69.5 °
Stem length	90.0 mm
Toptube	625 mm
Transmission	1x 12-speed
Travel	120 mm
Type	full suspension
Wheel distance	1175 mm
Wheel size	29 "

### More product images

