



CONWAY MTB full suspension "RLC FS 6.9" Mod. 23

full suspension, 29", topaz metallic fade / red, 12-speed SHIMANO "XT", 43 cm / S

RRP €3,499.95

The "RLC FS 6.9" comes up with more travel - and thus qualifies as a true marathon and downcountry bike. All bumps and uneven surfaces that come in front of the CONWAY "RLC FS 6.9" on cross-country or marathon trails are smoothed out with 120mm. To ensure full power transmission, the full-carbon race full suspension is light and laterally stiff. Your drive is provided by the SHIMANO "Deore XT Shadow Plus" shifting system with its 12 gears. From the same family come the hydraulic disc brakes. The lug tread of the tire combination of SCHWALBE, front "Racing Ray" and rear "Racing Ralph" in Evo quality, 60mm width with Addix Compound, gives you enough grip on loose ground. The DT SWISS "X 1900 Spline" wheels contribute to the lateral stiffness and plenty of drive power. The genes of the race full suspension bike come from the CONWAY siblings "WME" and "RLC", its handling is correspondingly sporty, the seating position nevertheless suitable for long distances. The "RLC FS" series is also prepared for the FOX "Livevalve" suspension systems.

Basic Data

Supplier Article Number:	BK23HA0282
EAN	4251971103221
MSRP:	€3,499.95
Bidex-Code	101020
DST-Code	1E00
Fedas-Code	154040
SB-Article	No
Brand/Supplier	CONWAY
Unit of measure:	PIECE
Weight	12.2 kg

Technical Data

Brake system	hydraulic disc brake
Chainstay	445 mm
Colour designation	topaz metallic fade / red
Drive	chain
E-bike	no
Features	damper , suspension fork
Frame height	43 cm
Frame shape	full suspension

Frame size	S
Frame travel	100 mm
Gears	12-speed
Gender	gents
Main colour	green
Material 1	carbon
Model range	RLC
Permissible system weight	130 kg
Reach	424 mm
Seat angle	72.0 °
Seat tube	425 mm
Secondary colour	red
Shifting name	12-Gang SHIMANO "XT"
Shifting type	derailleur shifting
Stack	586 mm
Steering tube	95 mm
Steering tube angle	69.5 °
Stem length	60.0 mm
Toptube	575 mm
Transmission	1x 12-speed
Travel	120 mm
Type	full suspension
Wheel distance	1119 mm
Wheel size	29 "

More product images

