



## CONWAY MTB full suspension "RLC FS 6.9" Mod. 23

full suspension, 29", topaz metallic fade / red, 12-speed SHIMANO "XT", 47 cm / M

**RRP €3,499.95**

The "RLC FS 6.9" comes up with more travel - and thus qualifies as a true marathon and downcountry bike. All bumps and uneven surfaces that come in front of the CONWAY "RLC FS 6.9" on cross-country or marathon trails are smoothed out with 120mm. To ensure full power transmission, the full-carbon race full suspension is light and laterally stiff. Your drive is provided by the SHIMANO "Deore XT Shadow Plus" shifting system with its 12 gears. From the same family come the hydraulic disc brakes. The lug tread of the tire combination of SCHWALBE, front "Racing Ray" and rear "Racing Ralph" in Evo quality, 60mm width with Addix Compound, gives you enough grip on loose ground. The DT SWISS "X 1900 Spline" wheels contribute to the lateral stiffness and plenty of drive power. The genes of the race full suspension bike come from the CONWAY siblings "WME" and "RLC", its handling is correspondingly sporty, the seating position nevertheless suitable for long distances. The "RLC FS" series is also prepared for the FOX "Livevalve" suspension systems.

### Basic Data

Supplier Article Number:	BK23HA0284
EAN	4251971103238
MSRP:	€3,499.95
Bidex-Code	101020
DST-Code	1E00
Fedas-Code	154040
SB-Article	No
Brand/Supplier	CONWAY
Unit of measure:	PIECE
Weight	12.2 kg

### Technical Data

Brake system	hydraulic disc brake
Chainstay	445 mm
Colour designation	topaz metallic fade / red
Drive	chain
E-bike	no
Features	damper , suspension fork
Frame height	47 cm
Frame shape	full suspension

<b>Frame size</b>	M
<b>Frame travel</b>	100 mm
<b>Gears</b>	12-speed
<b>Gender</b>	gents
<b>Main colour</b>	green
<b>Material 1</b>	carbon
<b>Model range</b>	RLC
<b>Permissible system weight</b>	130 kg
<b>Reach</b>	449 mm
<b>Seat angle</b>	72.0 °
<b>Seat tube</b>	465 mm
<b>Secondary colour</b>	red
<b>Shifting name</b>	12-Gang SHIMANO "XT"
<b>Shifting type</b>	derailleur shifting
<b>Stack</b>	595 mm
<b>Steering tube</b>	105 mm
<b>Steering tube angle</b>	69.5 °
<b>Stem length</b>	75.0 mm
<b>Toptube</b>	600 mm
<b>Transmission</b>	1x 12-speed
<b>Travel</b>	120 mm
<b>Type</b>	full suspension
<b>Wheel distance</b>	1147 mm
<b>Wheel size</b>	29 "

### More product images

