



CONTEC Rear Hub "Core CL"

12-speed Shimano Micro Spline, mounting width 148 mm (booster), approx. 405 g

RRP €79.95

With our Core hubs, you can build your wheels reliably and robustly for all the challenges of daily use. Their outstanding quality also makes them ideal for use on e-bikes. Made from aluminum, the Core rear hub offers 32 spoke holes, Center Lock brake disc mount, 12 mm Thru Axle and is designed for an installation width of 148 mm (Boost). The Microspline steel Freewheel Body is deliberately designed for robustness and durability, as is the use of high-quality ball bearings. The ratchets freehub system with 27 teeth and 3 Pawls offers fast interaction between the freehub and hub body, so that your pedal stroke is quickly converted into propulsion.

Basic Data

Supplier Article Number:	CL-TP-1 MICROSPLINE
EAN	4251971137981
MSRP:	€79.95
Fedas-Code	160452
SB-Article	No
Bidex-Code	204030
DST-Code	2P04
Brand/Supplier	CONTEC
Unit of measure:	PIECE
Weight	0.405 kg

Technical Data

Axle	12mm full-floating axle
Bearing type	ball bearing
Brake mounting	disc - Center Lock
Brake track	no , yes
Chainline	44.5 mm
E-bike type	ready
Flange diameter	68 mm
For wheel	standard
Freehub system	27
Freewheel body	Micro Spline
Freewheel body material	steel
Gears	12-speed
Hub body material	Aluminium
Hub model	Core CL
Installation width	148 mm (Boost)
Main colour	black
Mounting	rear wheel
Number of pawls	3 pcs.

Number of spoke holes	32 holes
Spoke hole diameter	for 2.00 and 2.34 mm
Spoke type	J-Bend
Type	cassette
Variant	Article