



CONTEC Aluminium Rim "Xeta"

25-622, 608 mm ERD (measured incl. spoke holes), 16.3 mm high, 25 mm inner width, 29.3 mm outer width, approx. 569 g

Price: €19.99

The ideal basis for building a tubeless-ready Wheel for 29" wheels with 32 Spokes. Thanks to the hollow chamber design, the Xeta Max rims made of 6063 aluminum are particularly light and stable. In the finished Wheel, these rims are suitable for a system weight of up to 150 kg. With an inner rim width of 25 mm, tires ranging in size from 42 to 62 mm fit on the rim. The single eyeletted nipple holes ensure additional durability of the rim by reducing the friction between the Spoke Nipple and the rim and also prevent the Nipples from working their way into the rim. The Xeta Max rim is only suitable for wheels with disc brakes. You can find suitable tubeless rim tapes in our CONTEC range.

Basic Data

Supplier Article Number:	30008498
EAN	4251971141117
MSRP:	€39.95
Bidex-Code	204010
Fedas-Code	160464
DST-Code	2P02
SB-Article	No
Brand/Supplier	CONTEC
Unit of measure:	PIECE
Weight	0.55 kg

Technical Data

Brake compatibility rim	disc
Brake mounting	disc - 5-hole , disc - 6-hole , disc - Center Lock , drum brake , roller brake
Brake track	no
Design	doublewall
ETRTO	25-622
For wheel	yes
Height	16.0 cm
Main colour	black
Number of spoke holes	32 holes

Permissible system weight	150 kg
Rim model	Xeta
Spoke Hole	easy eyelets
Text wheel configurator	suitable for E-bike
Tubeless system	tubeless ready
Valve type	Sclaverand (SV)
Variant	Article
Wheel size	28 / 29 "
Width	29.3 cm

More product images

