



CONTEC Aluminium Rim "Exit"

23-584, 571 mm ERD (incl. spoke holes measured), 16.2 mm high, 23.2 mm inner width, 28.3 mm outer width, approx. 532 g

RRP €29.95

A robust rims for building a classic wheel for 27.5" wheels with 32 spokes. Thanks to the hollow chamber design, the 6063 aluminum rims are particularly light and stable. In the finished Wheel, these rims are suitable for a system weight of up to 150 kg. With an inner rim width of 23 mm, tires ranging in size from 37 to 62 mm fit on the rim. The single eyeletted nipple holes ensure additional durability of the rim by reducing the friction between the Spoke Nipple and the rim and also prevent the Nipples from working their way into the rim. The Exit rim is only suitable for wheels with disc brakes.

Basic Data

Supplier Article Number:	30002551
EAN	4251971141155
MSRP:	€29.95
Bidex-Code	204010
Fedas-Code	160464
DST-Code	2P02
SB-Article	No
Brand/Supplier	CONTEC
Unit of measure:	PIECE
Weight	0.532 kg

Technical Data

Brake compatibility rim	disc
Brake mounting	disc - 5-hole , disc - 6-hole , disc - Center Lock , drum brake , roller brake
Brake track	no
Design	doublewall
E-bike type	ready
ETRTO	23-584
Effective Rim Diameter	571 mm
Eyelet color	silver
For wheel	yes
Height	16.0 cm
Hollow chamber shape	symmetrical
Main colour	black
Number of spoke holes	32 holes
Permissible system weight	150 kg
Rim height	16 mm
Rim inner width	23 mm
Rim outer width	28 mm
Spoke Hole	easy eyelets

Spoke hole diameter	for 2.00 mm
Text wheel configurator	suitable for E-bike
Valve type	Sclaverand (SV)
Variant	Article
Wheel size	27,5 "
Width	28.3 cm
max. spoke tension	1.200 Nm

More product images

