



CONTEC Rear Wheel "Xeta + CONTEC Core CL "

29" Rear Wheel

RRP €139.95

Our Xeta Core 30 29" Boost Rear Wheel, featuring a SHIMANO Micro Spline Freewheel Body, will win you over with its exceptional durability in the face of both major and minor challenges you encounter during sporty rides or on everyday trails. With a maximum system weight capacity of up to 150 kg, our Wheel has plenty of headroom for demanding rides, heavier Fahrers, and modern E-MTBs. The aluminum Core rear hub, featuring a Centerlock brake disc mount and a 12 mm Thru Axle, boasts a proven, robust design for minimal maintenance. The freewheel body for Shimano Micro Spline is made of robust CrMo steel for exceptional durability. 32 bent 2 mm stainless steel spokes also guarantee a high load capacity and thus the longevity of this wheel. The Xeta Max aluminium rim is tubeless-ready and, with a 30 mm inner rim width, is ideally suited for high-volume tires. All CONTEC wheels are assembled by experienced specialists at our wheel manufacturing facility in Hoya, Lower Saxony (Germany), and perfectly trued for you using state-of-the-art technology.

Basic Data

Supplier Article Number:	F=3498164 N=7476223
EAN	4251971142954
MSRP:	€139.95
Bidex-Code	204060
DST-Code	2P01
SB-Article	No
Fedas-Code	160462
Brand/Supplier	CONTEC
Unit of measure:	PIECE
Weight	1.2 kg

Technical Data

Axle	12mm full-floating axle
Brake mounting	disc - Center Lock
Brake system	for disc brake, Center Lock
Design	doublewall
E-bike type	ready
ETRTO	30-622
For wheel	yes
Freewheel body	Micro Spline
Hub colour	black
Hub model	Core CL
Installation width	148 mm
Main colour	black
Mounting	rear wheel
Number of spoke holes	32 holes
Permissible system weight	150 kg
Range of application	MTB

Rim colour	black
Rim height	18.1 mm
Rim model	Xeta
Rim type	tubeless ready
Shifting system	12-speed
Spoke Hole	easy eyelets
Spoke colour	black
Spoke diameter	2,00 mm
Spoke length left	294 mm
Spoke length right	292 mm
Spoke material	stainless steel
System compatibility	12-speed
Tubeless system	tubeless ready
Valve type	Sclaverand (SV)
Variant	Article
Wheel size	28 / 29 "