

QiO Electric compact bike "EINS P-5" Mod. 24

unisex, 20", ice blue matt, 5-speed SHIMANO "Nexus" coaster brake, 48 cm

RRP: €4,199.00

Start your day with a relaxed ride to the bakery, through the fields or across the campsite on your QiO "EINS P-5" e-bike. The smart system from Bosch ensures a fully connected experience.The "EINS P-5" has optimally coordinated drive components: the Bosch "Performance Line" engine, a 545 Wh Battery and the "Intuvia 100" Display. The 5-speed Shimano "Nexus" hub gears and the low-maintenance Gates Straps transmit the power smoothly.With its small 20" wheels, the compact e-bike is maneuverable and ideal for narrow streets in the city. The suspended parallelogram seatpost offers comfort on cobblestones and is equipped with anti-theft protection.The compact design of the "EINS P-5" makes it easy to take with you - wherever you go. Whether in the car for a trip into the countryside or in the camper van for a big adventure. It is also indispensable for everyday use in the city. Thanks to the foldable Pedals and the rotating Handlebar, it fits into small niches and tight spaces. The combination of hub gears and Straps makes it virtually maintenance-free and ideal for commuters who just want to get going.

Basic Data

Supplier Article Number:	01722465
EAN	4251971142282
MSRP:	€4,199.00
Fedas-Code	159021
DST-Code	1A01
WEEE registration number	DE92509320
SB-Article	No
Bidex-Code	123040
Brand/Supplier	QiO
Unit of measure:	PIECE
Weight	26.5 kg

Technical Data

Article type	Electric compact bike
Battery capacity	545.0 Wh
Bosch Smart System	yes
Brake system	coaster brake , hydraulic disc brake
Colour designation	ice blue matt
Drive	belt
Drive system	BOSCH Performance Line

Drive version	middle motor
E-bike	yes
Engine power	250 W
Features	chain guard , deep entry , electronic sliding aid , fender , suspension seatpost , system carrier
Frame height	48 cm
Frame shape	unisex
Gears	5-speed
Gender	unisex
Main colour	blue
Material	aluminium
Model range	EINS
Permissible system weight	180 kg
Shifting name	5-Gang SHIMANO "Nexus" Rücktritt
Shifting type	internal gear shifting
Support	up to 25km/h
Type	compact bike
Wheel size	20 "

Specifications

Battery	BOSCH "PowerPack 545", 545 Wh
Battery Lock	CONTEC "PowerLoc"
Chain / belt	GATES "CDX"
Chain guard	CURANA "C+", 46 teeth
Chain ring / pulley	Gates "CDX", 46 teeth, belt line 45.5 mm
Charger	BOSCH 4 A
Crank	Stronglight "Magan 3B", 170 mm
Derailleur hanger	QIO Slider Dropout
Display	BOSCH "Intuvia 100", 4-stages, remote control, push aid
Engine	BOSCH "Performance Line" engine, max. 75 Nm
Fender	SKS "A 69 R"
Fork	Aluminum, tapered 1 1/4" - 1.5"
Frame	QIO EINS, Bosch Gen. 3, BES3, aluminum, 49.5 cm
Front brake	TRP "C1.8 HD-EU817", Post Mount
Front hub	URSUS "RD30", Center Lock, QR
Front light	CONTEC "DLUX 80 E+", 80 lux
Front rotor	TRP "TR-25", Ø 180 mm, Centerlock
Front tire	SCHWALBE "Super Moto-X", 62-406, Reflex
Grips	HERRMANS "Clik Original DD37"
Handlebar	ergotec "Lady Town", 620 mm, Ø 31.8 mm, 30° backsweep
Headset	TOKEN "TK255E-HJ01", IS52/40 / IS52/44
Pedals	UNION "SP-153", foldable
Rear brake	TRP "C1.8 HD-EU817"

Rear carrier	QIO "MIK HD"
Rear hub	SHIMANO "Nexus SG-C7002-5CD", 5-speed, 5-hole
Rear light	CONTEC "TL-335 E-Stop", stop light
Rear rotor	TEKTRO "TR160-47", Ø 160 mm, 5-hole
Rear tire	SCHWALBE "Super Moto-X", 62-406, Reflex
Remote	BOSCH "BRC3600", LED Remote
Rims	SCHÜRMANN "YAK DISC 25", 25-406, 36 holes, disc brake, black
Saddle	Selle Royal "Nuvola 5060", Relaxed
Seatpost	by,schulz "G.2 ST", Ø 34.9 mm, 400 mm long, 30 mm travel, 12 mm offset
Sensor	Pedal pressure measuring im Motor + speed sensor
Shifting lever	SHIMANO "Nexus SL-C7000-5"
Spokes	Niro, schwarz
Sprocket / pulley	Gates "CDX", 28 teeth
Stands	URSUS "R78 - King Mini"
Stem	BY.SCHULZ "Stem SDS", 1 1/8", 31.8 mm handlebar clamps, 70 mm long, angle 7°, black

More product images

