

QiO Electric compact bike "EINS P-E" Mod. 24

unisex, 20", ice blue matt, enviolo "TR", 48 cm

RRP: €4,499.00

The QiO "EINS P-E" compact e-bike is perfect for touring or shopping in the city. Thanks to the Bosch Smart System, it is fully networked and always up to date. The eBike Flow app enables communication between the "Performance Line" engine, the 545 Wh Battery and the Operating Unit. You can select riding modes, plan routes and record tours automatically. The results can be synchronized with health apps.The continuously variable Enviolo "TR" hub gears are perfect for overland tours and hilly terrain - together with the Bosch "Performance Line" engine, you can make sporty progress at up to 25 km/h. The compact design, foldable pedals and compressible Handlepost make it easy to store in small spaces or in a camper van.With 62 mm wide tires on 20" wheels and the Parallelogramm Suspension Seatposts, the e-bike offers a high level of comfort on paved paths through the city. The by.schulz seatpost is also equipped with anti-theft protection.

Basic Data

Supplier Article Number:	01722549
EAN	4251971142367
MSRP:	€4,499.00
Fedas-Code	159021
DST-Code	1A01
WEEE registration number	DE92509320
SB-Article	No
Bidex-Code	123040
Brand/Supplier	QiO
Unit of measure:	PIECE
Weight	27.3 kg

Technical Data

Battery capacity	545.0 Wh
Bosch Smart System	yes
Brake system	hydraulic disc brake
Colour designation	ice blue matt
Drive	belt
Drive system	BOSCH Performance Line
Drive version	middle motor

E-bike	yes
Engine power	250 W
Features	chain guard , deep entry , electronic sliding aid , fender , suspension seatpost , system carrier
Frame height	48 cm
Frame shape	unisex
Gears	stepless
Gender	unisex
Main colour	blue
Material	aluminium
Model range	EINS
Permissible system weight	180 kg
Shifting name	enviolo "TR"
Shifting type	internal gear shifting
Support	up to 25km/h
Type	compact bike
Wheel size	20 "

Specifications

Battery	BOSCH "PowerPack 545", 545 Wh
Battery Lock	CONTEC "PowerLoc"
Chain / belt	GATES "CDX"
Chain guard	CURANA "C+", 55 teeth
Chain ring / pulley	Gates "CDX", 55 teeth, belt line 45.5 mm
Charger	BOSCH 4 A
Crank	Stronglight "Magan 3B", 170 mm
Derailleur hanger	QIO Slider Dropout
Display	BOSCH "Kiox 300", 4-stages, remote control, push aid
Engine	BOSCH "Performance Line" engine, max. 75 Nm
Fender	SKS "A 69 R"
Fork	Aluminum, tapered 1 1/4" - 1.5"
Frame	QIO EINS, Bosch Gen. 3, BES3, aluminum, 49.5 cm
Front brake	TRP "C1.8 HD-EU817", Post Mount
Front hub	URSUS "RD30", Center Lock, QR
Front light	CONTEC "DLUX 80 E+", 80 lux
Front rotor	TRP "TR-25", Ø 180 mm, Centerlock
Front tire	SCHWALBE "Super Moto-X", 62-406, Reflex
Grips	HERRMANS "Clik Original DD37"
Handlebar	ergotec "Lady Town", 620 mm, Ø 31.8 mm, 30° backsweep
Headset	TOKEN "TK255E-HJ01", IS52/40 / IS52/44
Pedals	UNION "SP-153", foldable
Rear brake	TRP "C1.8 HD-EU817"
Rear carrier	QIO "MIK HD"

Rear hub	ENVIOLO "TR", stepless, 6-hole
Rear light	CONTEC "TL-335 E-Stop", stop light
Rear rotor	TRP "RS02M", Ø 160 mm, 6-hole
Rear tire	SCHWALBE "Super Moto-X", 62-406, Reflex
Remote	BOSCH "BRC3600", LED Remote
Rims	SCHÜRMANN "YAK DISC 25", 25-406, 36 holes, disc brake, black
Saddle	Selle Royal "Nuvola 5060", Relaxed
Seatpost	by,schulz "G.2 ST", Ø 34.9 mm, 400 mm long, 30 mm travel, 12 mm offset
Sensor	Pedal pressure measuring im Motor + speed sensor
Shifting lever	ENVIOLO "Twist Pure Display", stepless
Spokes	Niro, schwarz
Sprocket / pulley	Gates "CDX", 22 teeth
Stands	URSUS "R78 - King Mini"
Stem	BY.SCHULZ "Stem SDS", 1 1/8", 31.8 mm handlebar clamps, 70 mm long, angle 7°, black

More product images

