

# QiO Electric compact bike "EINS P-R" Mod. 24

**unisex, 20", lead metal, Rohloff 14 G "E-14", 48 cm**

## RRP: €6,499.00

The QiO "EINS P-R" is even smarter with the Bosch Smart System. All of the compact e-bike’s drive components are networked with one another and controlled via the eBike Flow app. This ensures the bike is always up to date, as new features and updates are installed automatically.The compact one-size frame is suitable for riders between 1.60 and 1.90 m tall. The Handlepost and Seatpost can be fine-tuned for the ideal riding experience. The “EINS P-R” impresses not only with its compact size but also with its high-quality features.The bike is equipped with a 14-speed Rohloff hub gear system, which is ideal for e-bikes with powerful engines. In addition, the Bosch “Kiox 500” Display shows all gear changes and helps you select the right drive level for the powerful “Performance Line” engine. The 725-Wh battery makes this compact e-bike perfect for long rides.With 62-mm-wide tires on 20-inch wheels and a Parallelogramm Suspension Seatpost, the bike offers a high level of comfort on various surfaces. The hydraulic disc brakes and high-quality Busch + Müller lighting round out the e-bike, equipping it with everything needed for everyday use in the city and in the countryside.

### Basic Data

| | |
|---|---|
| **Supplier Article Number:** | 01722572 |
| **EAN** | 4251971142398 |
| **MSRP:** | €6,499.00 |
| **Fedas-Code** | 159021 |
| **DST-Code** | 1A01 |
| **WEEE registration number** | DE92509320 |
| **SB-Article** | No |
| **Bidex-Code** | 123040 |
| **Brand/Supplier** | QiO |
| **Unit of measure:** | PIECE |
| **Weight** | 27.7 kg |

### Technical Data

| | |
|---|---|
| **Battery capacity** | 725.0 Wh |
| **Bosch Smart System** | yes |
| **Brake system** | hydraulic disc brake |
| **Colour designation** | lead metal |
| **Drive** | belt |
| **Drive system** | BOSCH Performance Line |
| **Drive version** | middle motor |

| | |
|---|---|
| **E-bike** | yes |
| **Engine power** | 250 W |
| **Features** | chain guard , deep entry , electronic sliding aid , fender , suspension seatpost , system carrier |
| **Frame height** | 48 cm |
| **Frame shape** | unisex |
| **Gears** | 14-speed |
| **Gender** | unisex |
| **Main colour** | grey |
| **Material** | aluminium |
| **Model range** | EINS |
| **Permissible system weight** | 180 kg |
| **Shifting name** | Rohloff 14 G "E-14" |
| **Shifting type** | internal gear shifting |
| **Support** | up to 25km/h |
| **Type** | compact bike |
| **Wheel size** | 20 " |

## Specifications

| | |
|---|---|
| **Battery** | BOSCH "PowerPack 725", 725 Wh |
| **Battery Lock** | CONTEC "PowerLoc" |
| **Chain / belt** | GATES "CDX" |
| **Chain guard** | Rohloff belt guard |
| **Chain ring / pulley** | Gates "CDX", 63 teeth, belt line 57.7 mm |
| **Charger** | BOSCH 4 A |
| **Crank** | Stronglight "Magan 3B", 170 mm |
| **Derailleur hanger** | QIO Slider Dropout Rohloff |
| **Display** | BOSCH "Kiox 500", 4-stages, Remote Control, push-aid |
| **Engine** | BOSCH "Performance Line" engine, max. 75 Nm |
| **Fender** | SKS "A 69 R" |
| **Fork** | Aluminum, tapered 1 1/4" - 1.5" |
| **Frame** | QIO EINS, Bosch Gen. 3, BES3, aluminum, 49.5 cm |
| **Front brake** | TRP "C1.8 HD-EU817", Post Mount |
| **Front hub** | URSUS "RD30", Center Lock, QR |
| **Front light** | Busch + Müller "IQ-XS E Highbeam", 100 Lux |
| **Front rotor** | TRP "TR-25", Ø 180 mm, Centerlock |
| **Front tire** | SCHWALBE "Super Moto-X", 62-406, Reflex |
| **Grips** | HERRMANS "Clik Original DD37" |
| **Handlebar** | ergotec "Lady Town", 620 mm, Ø 31.8 mm, 30° backsweep |
| **Handlepost** | BY.SCHULZ "Twist", Ø 28.6 mm, 1 1/4", T17 |
| **Headset** | TOKEN "TK255E-HJ01", IS52/40 / IS52/44 |
| **Pedals** | UNION "SP-153", foldable |
| **Rear brake** | TRP "C1.8 HD-EU817" |

| | |
|---|---|
| **Rear carrier** | QIO "MIK HD" |
| **Rear hub** | ROHLOFF "Speedhub 500/14", 4-hole, QR |
| **Rear light** | CONTEC "TL-335 E-Stop", stop light |
| **Rear rotor** | MAGURA "STORM SL", Ø 160mm, 4-hole, for Rohloff speedhub |
| **Rear tire** | SCHWALBE "Super Moto-X", 62-406, Reflex |
| **Remote** | BOSCH "BRC3600", LED Remote |
| **Rims** | DT SWISS "U 663", 36 hole, eyeletted, tubeless ready |
| **Saddle** | Selle Royal "Nuvola 5060", Relaxed |
| **Seatpost** | by,schulz "G.2 ST", Ø 34.9 mm, 400 mm long, 30 mm travel, 12 mm offset |
| **Sensor** | Pedal pressure measuring im Motor + speed sensor |
| **Shifting lever** | Rohloff, 14-speed |
| **Spokes** | Niro, schwarz |
| **Sprocket / pulley** | Gates "CDX", 20 teeth |
| **Stands** | URSUS "R78 - King Mini" |
| **Stem** | BY.SCHULZ "Stem SDS", 1 1/8", 31.8 mm handlebar clamps, 70 mm long, angle 7°, black |

## More product images

