

QiO Electric compact bike "EINS P-R" Mod. 24

unisex, 20", ice blue matt, Rohloff 14 G "E-14", 48 cm

RRP: €6,499.00

The QiO "EINS P-R" is even smarter with the Bosch Smart System. All of the compact e-bike's drive components are networked with one another and controlled via the eBike Flow app. This ensures the bike is always up to date, as new features and updates are installed automatically.The compact one-size frame is suitable for riders between 1.60 and 1.90 m tall. The Handlepost and Seatpost can be fine-tuned for the ideal riding experience. The "EINS P-R" impresses not only with its compact size but also with its high-quality features.The bike is equipped with a 14-speed Rohloff hub gear system, which is ideal for e-bikes with powerful engines. In addition, the Bosch "Kiox 500" Display shows all gear changes and helps you select the right drive level for the powerful "Performance Line" engine. The 725-Wh battery makes this compact e-bike perfect for long rides.With 62-mm-wide tires on 20-inch wheels and a Parallelogramm Suspension Seatpost, the bike offers a high level of comfort on various surfaces. The hydraulic disc brakes and high-quality Busch + Müller lighting round out the e-bike, equipping it with everything needed for everyday use in the city and in the countryside.

Basic Data

Supplier Article Number:	01722622
EAN	4251971142442
MSRP:	€6,499.00
Fedas-Code	159021
DST-Code	1A01
WEEE registration number	DE92509320
SB-Article	No
Bidex-Code	123040
Brand/Supplier	QiO
Unit of measure:	PIECE
Weight	27.7 kg

Technical Data

Battery capacity	725.0 Wh
Bosch Smart System	yes
Brake system	hydraulic disc brake
Colour designation	ice blue matt
Drive	belt
Drive system	BOSCH Performance Line
Drive version	middle motor

E-bike	yes
Engine power	250 W
Features	chain guard , deep entry , electronic sliding aid , fender , suspension seatpost , system carrier
Frame height	48 cm
Frame shape	unisex
Gears	14-speed
Gender	unisex
Main colour	blue
Material	aluminium
Model range	EINS
Permissible system weight	180 kg
Shifting name	Rohloff 14 G "E-14"
Shifting type	internal gear shifting
Support	up to 25km/h
Type	compact bike
Wheel size	20 "

Specifications

Battery	BOSCH "PowerPack 725", 725 Wh
Battery Lock	CONTEC "PowerLoc"
Chain / belt	GATES "CDX"
Chain guard	Rohloff belt guard
Chain ring / pulley	Gates "CDX", 63 teeth, belt line 57.7 mm
Charger	BOSCH 4 A
Crank	Stronglight "Magan 3B", 170 mm
Derailleur hanger	QIO Slider Dropout Rohloff
Display	BOSCH "Kiox 500", 4-stages, Remote Control, push-aid
Engine	BOSCH "Performance Line" engine, max. 75 Nm
Fender	SKS "A 69 R"
Fork	Aluminum, tapered 1 1/4" - 1.5"
Frame	QIO EINS, Bosch Gen. 3, BES3, aluminum, 49.5 cm
Front brake	TRP "C1.8 HD-EU817", Post Mount
Front hub	URSUS "RD30", Center Lock, QR
Front light	Busch + Müller "IQ-XS E Highbeam", 100 Lux
Front rotor	TRP "TR-25", Ø 180 mm, Centerlock
Front tire	SCHWALBE "Super Moto-X", 62-406, Reflex
Grips	HERRMANS "Clik Original DD37"
Handlebar	ergotec "Lady Town", 620 mm, Ø 31.8 mm, 30° backsweep
Handlepost	BY.SCHULZ "Twist", Ø 28.6 mm, 1 1/4", T17
Headset	TOKEN "TK255E-HJ01", IS52/40 / IS52/44
Pedals	UNION "SP-153", foldable
Rear brake	TRP "C1.8 HD-EU817"

Rear carrier	QIO "MIK HD"
Rear hub	ROHLOFF "Speedhub 500/14", 4-hole, QR
Rear light	CONTEC "TL-335 E-Stop", stop light
Rear rotor	MAGURA "STORM SL", Ø 160mm, 4-hole, for Rohloff speedhub
Rear tire	SCHWALBE "Super Moto-X", 62-406, Reflex
Remote	BOSCH "BRC3600", LED Remote
Rims	DT SWISS "U 663", 36 hole, eyeletted, tubeless ready
Saddle	Selle Royal "Nuvola 5060", Relaxed
Seatpost	by,schulz "G.2 ST", Ø 34.9 mm, 400 mm long, 30 mm travel, 12 mm offset
Sensor	Pedal pressure measuring im Motor + speed sensor
Shifting lever	Rohloff, 14-speed
Spokes	Niro, schwarz
Sprocket / pulley	Gates "CDX", 20 teeth
Stands	URSUS "R78 - King Mini"
Stem	BY.SCHULZ "Stem SDS", 1 1/8", 31.8 mm handlebar clamps, 70 mm long, angle 7°, black

More product images

