



CONWAY Electric MTB full suspension "Ryvon LT 10.0" Mod. 24

full suspension, 29", bronze metallic matt / orange, 12-speed SRAM "X0 AXS T-Type", 40 cm / S

RRP €9,999.95

The Conway RYVON LT 10.0 e-enduro bike is the ultimate off-road machine, designed to take your off-road adventures to a whole new level. With innovative German engineering, high-quality components and a performance that will inspire you, this bike sets new scales in the field of E-MTBs. The RYVON LT 10.0 features a removable battery concept that offers higher energy density and incredibly fast charging times. This means you can enjoy and extend your time on the trails more without having to worry about battery life. We know that comfort and ergonomics are key to getting the most out of your rides. That's why the RYVON LT 10.0 features our Ergonomic Sizing System. With coordinated grip diameters, stem lengths, handlebar widths and crank lengths that vary depending on the frame size, you can be sure that this bike will fit you perfectly. At the heart of the RYVON LT 10.0 is the powerful Light-E MTB engine, which gives you the power you need for the steepest climbs and challenging descents. Together with high-end spec equipment such as the SRAM "X0 Eagle AXS T-Type" drivetrain, maximum performance is guaranteed. The Eagle Transmission is light, robust and shifts precisely - even under full load. The RYVON LT 10.0 is a light e-enduro bike that is characterized by its completely newly developed frame. This frame heralds a new generation of frame platforms and design language at CONWAY. The striking lines and innovative battery concept make it clear that this bike is made for the future. With Long Travel suspension, it is ready to tackle even the roughest off-road conditions.

Basic Data

Supplier Article Number:	01025352
EAN	4251971145740
MSRP:	€9,999.95
Fedas-Code	154050
WEEE registration number	DE92509320
DST-Code	1E01
SB-Article	No
Bidex-Code	121020
Brand/Supplier	CONWAY
Unit of measure:	PIECE
Weight	19 kg

Technical Data

Battery capacity	400.0 Wh
Brake system	hydraulic disc brake
Category E-bike	4
Chainstay	442 mm

Child Seat Approval	no
Colour designation	bronze metallic matt / orange
Drive	chain
Drive system	BOSCH Performance Line SX
Drive version	middle motor
E-bike	yes
Engine power	250 W
Features	damper , electronic sliding aid , suspension fork
Frame height	40 cm
Frame shape	full suspension
Frame size	S
Frame travel	170 mm
Gears	12-speed
Gender	gents
Main colour	gold
Material 1	carbon
Model range	Ryvon
Permissible system weight	140 kg
Reach	440 mm
Seat angle	77.4 °
Seat tube	400 mm
Secondary colour	orange
Shifting name	12-Gang SRAM "X0 AXS T-Type"
Shifting type	derailleur shifting
Stack	618 mm
Steering tube	100 mm
Steering tube angle	63.5 °
Stem length	32.0 mm
Support	up to 25km/h
Toptube	573 mm
Trailer Approval	no
Transmission	1x 12-speed
Travel	170 mm
Type	full suspension
Wheel distance	1227 mm
Wheel size	29 "

More product images



Einsatzzweck / Kategorie

Der Einsatzzweck, für den für E-Bike konzipiert ist, ergibt sich aus der jeweiligen Kategorie (1-6 gemäß EN 17406). Die Kategorie, die im E-Bike zugewiesen ist, entnehmen Sie dem Übergangsschild (siehe dem Typenschild) Ihres E-Bikes.

Kategorie / Einsatzzweck	1	2	3	4	5	6
Kategorie / Einsatzzweck						
EN 17406	EN 17406	EN 17406	EN 17406	EN 17406	EN 17406	EN 17406
Typischer Einsatz	Reisefahrrad, Trekking, urbaner, enduroer, Adventure	Endurofahrrad, Trekking, urbaner, Adventure	Sport-/Wettbewerb, Offroad mit niedrigem bis hohem Anspruch an Steig	Sport-/Wettbewerb, Offroad mit hohem bis sehr hohem Anspruch an Steig	Extremesport	Sport-/Wettbewerb, Offroad mit hoher Anforderung
Abhängige Einstellparameter	Keine Einstellparameter	Wie Kategorie 1 und geschweifte Klammern	Wie Kategorie 1 und geschweifte Klammern	Wie Kategorie 1, 2 und 3, geschweifte Klammern	Keine Einstellparameter	Wie Kategorie 1 und 2, geschweifte Klammern
Typischer Rahmenhöhe	< 15 cm	< 15 cm	< 80 cm	< 120 cm	> 120 cm	< 15 cm
Typischer Rahmenhöhe	15-25 km/h	15-25 km/h	nicht relevant	nicht relevant	nicht relevant	30-50 km/h