

VICTORIA Electric trekking bike "Manoc 6" Mod. 24

wave, 28", galaxy white, 1x11-speed SHIMANO "Deore XT"/"Deore SLX", 58 cm / XL

RRP: €4,699.00

The top derailleur model in the MANOC premium trekking series is the ideal partner for long-distance touring.The smart Bosch system delivers the maximum of what is currently possible with the "Performance CX" drives and the highest-capacity "PowerTube 750" Battery. Additional information that the "Kiox 300" color display does not provide can be transmitted to your smartphone via the eFlow Bike app. Other apps, such as Komoot or Strava, then use the information for navigation and route planning.With its 80 mm of travel, the air-sprung Fork offers plenty of comfort and absorbs any bumps in the road from the wide, low rolling resistance tires.The eleven gears come from a Shimano "Deore XT" rear derailleurs. This, as well as the chain and cassette, come from the Linkglide series and are around three times more wear-resistant and comfortable than a comparable standard Hyperglide version.As with all new Victoria developments, the batteries integrated in the down tube can be removed from the top, making it unnecessary to remove them from the bottom. However, in view of the large capacities and the associated battery weight, we recommend charging at the MANOC instead, as it is simply more convenient.With a permissible total weight of 170 kg, the MANOC 6 is the ideal touring companion and, thanks to the MIK luggage carrier system, can firmly attach panniers and the like without them slipping during the ride.

Basic Data

Supplier Article Number:	BK23HV0560
EAN	4251971110113
MSRP:	€4,699.00
WEEE registration number	DE92509320
DST-Code	1B01
SB-Article	No
Bidex-Code	122010
Fedas-Code	155021
Brand/Supplier	VICTORIA
Unit of measure:	PIECE
Weight	28.8 kg

Technical Data

Battery capacity	750.0 Wh
Bosch Smart System	yes
Brake system	hydraulic disc brake
Colour designation	galaxy white
Drive	chain

Drive system	BOSCH Performance Line CX
Drive version	middle motor
E-bike	yes
Engine power	250 W
Features	chain guard , electronic sliding aid , fender , frame lock , suspension fork
Frame height	58 cm
Frame shape	wave
Frame size	XL
Gears	11-speed
Gender	ladies
Main colour	white
Material	aluminium
Model range	Manoc
Permissible system weight	170 kg
Shifting name	1x11-Gang SHIMANO "Deore XT"/"Deore SLX"
Shifting type	derailleur shifting
Support	up to 25km/h
Transmission	1x 11-speed
Travel	80 mm
Type	trekking bike
Wheel size	28 "

Specifications

Battery	BOSCH "Powertube 750", Lithium-Ionen mit BMS, 750 Wh
Bottom bracket	BOSCH
Brake	TEKTRO "HD-T390"
Brake lever	TEKTRO "HD-T390"
Chain / belt	SHIMANO "CN-HG601"
Chain guard	HESLING "Velo" Bosch Gen.4
Chain ring / pulley	FSA, 38 Z.
Charger	BOSCH 4 Ah
Crank	FSA "CK-745", Gen.4
Derailleur hanger	Slider Dropout
Display	BOSCH "Kiox 300"
Engine	BOSCH "Performance CX", 36 V, 250 W
Fender	CURANA "Apollo", 60mm, schwarz matt, Spoiler
Fork	RST 2022 "VIVair E-15 TNL", 700Cx300 mm, tapered, ohne Gewinde, 80 mm Federweg, PM-Disc, QPQ, Schutzblechaufnahme, schwarz matt
Frame	Bosch-Intube-Frame, Aluminium 6061
Frame Lock	Contec "Powerloc L AZ"
Front hub	SHIMANO "HB-TC500", 15x100 mm
Front light	CONTEC "Dlux 120 E+" 120 Lux

Front rotor	TEKTRO "TR180-45", 180mm, Center-Lock
Front tire	CONTINENTAL "Contact Plus" 50-622
Grips	CONTEC "Merge Trekking Ergo"
Handlebar	ERGOTEC " Rise Bar 50 Comfort", 720 mm, Ø 31,8 mm, schwarz, Level 6
Pedals	UNION "SP-828", Alu, Antislip
Rear carrier	MASSLOAD MIK
Rear derailleur	SHIMANO "Deore XT RD-M8130", 11-fach
Rear hub	SHIMANO FH-MT400-B,, 12x148 mm
Rear light	CONTEC „TL-335 E-Stop“, mit Stoplicht
Rear rotor	TEKTRO "TR180-45", 160mm, Center-Lock
Rear tire	CONTINENTAL "Contact Plus" 50-622
Remote	BOSCH "BRC3600"
Rims	MACH "650 Disc"
Saddle	SELLE ROYAL "Orbis" Relax
Seatpost	ERGOTEC Hook, 31.6mm, 400mm, Level 6
Sensor	Pedal pressure measuring im Motor + speed sensor
Shifting lever	SHIMANO "Deore XT SL-M8130-IR11"
Spokes	Niro, 2 mm, schwarz
Sprocket / pulley	SHIMANO "CS-LG700-11 " 11-50 Z. silber
Stands	URSUS "King2", Hinterbau, 40 mm, verstellbar
Stem	ERGOTEC "Swell-R Ahead 70", Ø31,8 mm, 45 °, schwarz 120mm + 5mm Spacer