



## QiO Electric compact bike "EINS AP-8R" (#1)

unisex, 20", ice blue matt, 8-speed SHIMANO "Nexus" freewheel, 48 cm

**Price: €2,520.00**

The QiO "EINS AP-8R" is the sister model of the "EINS AP-8" and offers even lower maintenance. In addition to the virtually maintenance-free hub gears, it is equipped with a Gates CDC Straps. The "EINS AP-8R" is ideal for simply getting on and riding off, whether for commuting or spontaneous tours. A new feature is the "Purion 200" Display, which shows all the important information at a glance. The Bosch "Active Line Plus" engine provides harmonious support up to 25 km/h and is powered by a 400 Wh "PowerPack". The Battery can be easily removed and recharged. The 8-speed Shimano "Nexus" gear hub is particularly low-maintenance. Thanks to the bright LED Front Light and Rear Light with stop light function integrated in the Carrier, you are safe on the road in the evening. The Stem can be rotated by 90° and the Pedals can be folded down to save space. The maximum rider weight is 120 kg.

### Basic Data

Supplier Article Number:	01723220
EAN	4251971163645
MSRP:	€3,499.00
Fedas-Code	159021
DST-Code	1A01
WEEE registration number	DE92509320
SB-Article	No
Bidex-Code	123040
Brand/Supplier	QiO
Unit of measure:	PIECE
Weight	26.2 kg

### Technical Data

Access height	182 mm
Battery capacity	400.0 Wh
Bosch Smart System	yes
Brake system	hydraulic rim brake
Chainstay	451 mm
Colour designation	ice blue matt
Drive	belt
Drive system	BOSCH Active Line Plus

<b>Drive version</b>	middle motor
<b>E-bike</b>	yes
<b>Engine power</b>	250 W
<b>Features</b>	chain guard , deep entry , electronic sliding aid , fender , system carrier
<b>Frame height</b>	48 cm
<b>Frame shape</b>	unisex
<b>Gears</b>	8-speed
<b>Gender</b>	unisex
<b>Length</b>	1685 mm
<b>Main colour</b>	blue
<b>Material 1</b>	aluminium
<b>Model range</b>	EINS
<b>Passage width</b>	190 mm
<b>Permissible system weight</b>	180 kg
<b>Reach</b>	408 mm
<b>Seat angle</b>	70.5 °
<b>Seat tube</b>	48 mm
<b>Shifting name</b>	8-Gang SHIMANO "Nexus" Leerlauf
<b>Shifting type</b>	internal gear shifting
<b>Stack</b>	541 mm
<b>Steering tube</b>	220 mm
<b>Steering tube angle</b>	71.0 °
<b>Stem length</b>	70.0 mm
<b>Support</b>	up to 25km/h
<b>Toptube</b>	576 mm
<b>Type</b>	compact bike
<b>Wheel distance</b>	1108 mm
<b>Wheel size</b>	20 "

### More product images

