



QiO Electric compact bike "EINS AP-8R" (#1)

unisex, 20", forest green, 8-speed SHIMANO "Nexus" coaster brake, 48 cm

Price: €2,520.00

The QiO "EINS AP-8R" is the sister model of the "EINS AP-8" and offers even lower maintenance. In addition to the virtually maintenance-free hub gears, it is equipped with a Gates CDC Straps. The "EINS AP-8R" is ideal for simply getting on and riding off, whether for commuting or spontaneous tours. A new feature is the "Purion 200" Display, which shows all the important information at a glance. The Bosch "Active Line Plus" engine provides harmonious support up to 25 km/h and is powered by a 400 Wh "PowerPack". The Battery can be easily removed and recharged. The 8-speed Shimano "Nexus" gear hub is particularly low-maintenance. Thanks to the bright LED Front Light and Rear Light with stop light function integrated in the Carrier, you are safe on the road in the evening. The Stem can be rotated by 90° and the Pedals can be folded down to save space. The maximum rider weight is 120 kg.

Basic Data

Supplier Article Number:	01723287
EAN	4251971163706
MSRP:	€3,499.00
Fedas-Code	159021
DST-Code	1A01
WEEE registration number	DE92509320
SB-Article	No
Bidex-Code	123040
Brand/Supplier	QiO
Unit of measure:	PIECE
Weight	26.2 kg

Technical Data

Access height	182 mm
Battery capacity	400.0 Wh
Bosch Smart System	yes
Brake system	coaster brake , hydraulic disc brake
Chainstay	451 mm
Colour designation	forest green
Drive	belt
Drive system	BOSCH Active Line Plus

Drive version	middle motor
E-bike	yes
Engine power	250 W
Features	chain guard , deep entry , electronic sliding aid , fender , system carrier
Frame height	48 cm
Frame shape	unisex
Gears	8-speed
Gender	unisex
Length	1685 mm
Main colour	green
Material 1	aluminium
Model series	EINS
Passage width	190 mm
Permissible system weight	180 kg
Reach	408 mm
Seat angle	70.5 °
Seat tube	48 mm
Shifting name	8-Gang SHIMANO "Nexus" Rücktritt
Shifting type	internal gear shifting
Stack	541 mm
Steering tube	220 mm
Steering tube angle	71.0 °
Stem length	70.0 mm
Support	up to 25km/h
Toptube	576 mm
Type	compact bike
Wheel distance	1108 mm
Wheel size	20 "