

QiO Electric compact bike "EINS P-5" (#1)

unisex, 20", lead metal, 5-speed SHIMANO "Nexus" freewheel, 48 cm

RRP: €4,199.00

Start your day relaxed with the QiO "EINS P-5" e-bike. Whether it's to the bakery, through the fields or across the campsite - the smart Bosch system (BES3) ensures a fully connected ride.The "EINS P-5" offers the Bosch "Performance Line" engine, a 545 Wh Battery and the "Intuvia 100" Display. The 5-speed Shimano "Nexus" hub gears and the low-maintenance Gates CDC Straps guarantee smooth power transmission. With its 20" wheels, the e-bike is maneuverable and ideal for narrow city streets, where the sprung parallelogram seatposts offer plenty of comfort and are theft-proof.The compact design makes it easy to take with you, whether in the car or camper van. Foldable pedals and rotating Handlebars save space. Ideal for commuters who just want to get going.

Basic Data

Supplier Article Number:	01723334
EAN	4251971163751
MSRP:	€4,199.00
Fedas-Code	159021
DST-Code	1A01
WEEE registration number	DE92509320
SB-Article	No
Bidex-Code	123040
Brand/Supplier	QiO
Unit of measure:	PIECE
Weight	26.5 kg

Technical Data

Article type	Electric compact bike
Battery capacity	545.0 Wh
Bosch Smart System	yes
Brake system	hydraulic rim brake
Colour designation	lead metal
Drive	belt
Drive system	BOSCH Performance Line
Drive version	middle motor

E-bike	yes
Engine power	250 W
Features	chain guard , deep entry , electronic sliding aid , fender , suspension seatpost , system carrier
Frame height	48 cm
Frame shape	unisex
Gears	5-speed
Gender	unisex
Main colour	grey
Material	aluminium
Model range	EINS
Permissible system weight	180 kg
Shifting name	5-Gang SHIMANO "Nexus" Leerlauf
Shifting type	internal gear shifting
Support	up to 25km/h
Type	compact bike
Wheel size	20 "

Specifications

Battery	BOSCH "PowerPack 545", 545 Wh
Battery Lock	ABUS Battery Lock
Bottom bracket	BOSCH
Brake lever	TRP HD-EU817
Chain guard	CURANA "C+", 46 teeth
Chain ring / pulley	Gates "CDC", 46 teeth, belt line 45.5 mm
Charger	BOSCH 4 A
Crank	Stronglight "Magan 3B", 170 mm
Derailleur hanger	QIO Slider Dropout
Display	BOSCH "Intuvia 100", 4-stages, remote control, push aid
Engine	BOSCH "Performance Line" engine, max. 75 Nm
Fender	curana "Apollo Orbit 70"
Fork	Aluminum, tapered 1 1/4" - 1.5"
Frame	QIO EINS, Bosch Gen. 3, BES3, aluminum, 49.5 cm
Front brake	TRP "C1.8 HD-EU817", Post Mount
Front hub	SHIMANO "Deore HB-M5100," Center Lock, QR
Front light	Busch + Müller "Briq-S E", 60 lux
Front rotor	TRP "TR-25", Ø 180 mm, Centerlock
Front tire	CONTINENTAL "eContact Plus," 62-406, Reflex
Grips	HERRMANS "Nucore Town," wave
Handlebar	ergotec "Lady Town", 620 mm, Ø 31.8 mm, 30° backsweep
Headset	TOKEN "TK255E-HJ04", IS52/40 / IS52/44
Pedals	UNION "SP-153", foldable
Rear brake	TRP "C1.8 HD-EU817"

Rear carrier	"MIK HD 2.0" for MIK Side
Rear hub	SHIMANO "Nexus SG-C7000-5D", 5-speed, Center Lock
Rear light	Busch + Müller "Dart E Brex "
Rear rotor	TRP "TR-25", Ø 160 mm, Centerlock
Rear tire	CONTINENTAL "eContact Plus," 62-406, Reflex
Remote	BOSCH "BRC3600", LED Remote
Rims	DT SWISS "U 663", 36 hole, eyeletted, tubeless ready
Saddle	Selle Royal "On", Moderate Wide
Seatpost	by,schulz "G.2 ST", Ø 34.9 mm, 400 mm long, 30 mm travel, 12 mm offset
Sensor	Pedal pressure measuring im Motor + speed sensor
Shifting lever	SHIMANO "Nexus SL-C7000-5"
Spokes	DT-Swiss ELEMENTAL, schwarz
Sprocket / pulley	Gates "CDX", 28 teeth
Stands	URSUS "R78 - King Mini"
Stem	BY.SCHULZ "Stem SDS", 1 1/8", 31.8 mm handlebar clamps, 70 mm long, angle 7°, black

More product images

