



QiO Electric compact bike "EINS P-R" (#1)

unisex, 20", imola red matt, Rohloff 14 G "E-14", 48 cm

Price: €4,730.00

The QiO "EINS P-R" offers you a particularly intelligent riding experience. Thanks to the Bosch Smart System (BES3), all drive components of the compact e-bike are networked and controlled via the eBike Flow app. This means your bike is always up to date, as updates and new features are installed automatically. The 14-speed Rohloff gear hub is perfect for e-bikes with powerful drives - like this one. All gear changes are displayed on the Bosch "Kiox 500" Display. It also helps you select the right drive level for the powerful "Performance Line" engine. The 800 Wh Battery makes the compact e-bike ideal for long tours. With 62 mm wide tires on 20" wheels and the Parallelogramm Suspension Seatposts, the bike offers a high level of comfort on various surfaces. The hydraulic disc brakes and the high-quality Busch + Müller "IQ-XS high beam" lighting, including rear lights with stop light function integrated into the Carrier, round off the e-bike. Perfect for everyday use in the city and in the countryside.

Basic Data

Supplier Article Number:	01723634
EAN	4251971164291
MSRP:	€6,499.00
Fedas-Code	159021
DST-Code	1A01
WEEE registration number	DE92509320
SB-Article	No
Bidex-Code	123040
Brand/Supplier	QiO
Unit of measure:	PIECE
Weight	27.7 kg

Technical Data

Access height	182 mm
Battery capacity	800.0 Wh
Bosch Smart System	yes
Brake system	hydraulic disc brake
Chainstay	451 mm
Colour designation	imola red matt
Drive	belt

Drive system	BOSCH Performance Line
Drive version	middle motor
E-bike	yes
Engine power	250 W
Features	chain guard , deep entry , electronic sliding aid , fender , suspension seatpost , system carrier
Frame height	48 cm
Frame shape	unisex
Gears	14-speed
Gender	unisex
Length	1685 mm
Main colour	red
Material 1	aluminium
Model range	EINS
Passage width	190 mm
Permissible system weight	180 kg
Reach	408 mm
Seat angle	70.5 °
Seat tube	48 mm
Shifting name	Rohloff 14 G "E-14"
Shifting type	internal gear shifting
Stack	541 mm
Steering tube	220 mm
Steering tube angle	71.0 °
Stem length	70.0 mm
Support	up to 25km/h
Toptube	576 mm
Type	compact bike
Wheel distance	1108 mm
Wheel size	20 "

More product images

