



CONWAY Electric MTB full suspension "eWME 2.0" (#1)

full suspension, 29", bronze matt, 10-speed SHIMANO "Cues", 50 cm / XL

RRP €3,999.95

The Conway "eWME 2.0" is your new partner for exciting trails and challenging drives, providing plenty of riding fun with its powerful e-drive and well thought-out geometry. With a stable 29" Wheel and a weight of 25.8 kg, it is ready to master any trail adventure. Driven by the Shimano "Steps" mid-motor, the bike offers support up to 25 km/h and with its 720 Wh Battery, you are well equipped for long tours. The 1x10 chain drive with Shimano gears ensures that you always find the right gear, whether on steep climbs or fast descents. The hydraulic Disc Brakes bring you safely to a stop even on the steepest downhill. With a fork travel of 160 mm and a frame travel of 155 mm, the "eWME 2.0" is ideally equipped to enjoy all-mountain trails and single tracks and offer you a smooth riding experience. The head tube angle of 65° and the seat angle of 76° ensure a relaxed but aggressive riding position, while the chainstay length and wheelbase provide stability and maneuverability.

Basic Data

Supplier Article Number:	BK25HA0086
EAN	4251971168350
MSRP:	€3,999.95
Fedas-Code	154050
WEEE registration number	DE92509320
DST-Code	1E01
SB-Article	No
Bidex-Code	121020
Brand/Supplier	CONWAY
Unit of measure:	PIECE
Weight	25.8 kg

Technical Data

Battery capacity	720.0 Wh
Brake system	hydraulic disc brake
Category E-bike	3
Chainstay	456 mm
Child Seat Approval	no
Colour designation	bronze matt

Drive	chain
Drive system	SHIMANO STEPS EP8
Drive version	middle motor
E-bike	yes
Engine power	250 W
Features	damper , electronic sliding aid , suspension fork
Frame height	50 cm
Frame shape	full suspension
Frame size	XL
Frame travel	155 mm
Gears	10-speed
Gender	gents
Main colour	gold
Material 1	aluminium
Model range	eWME
Permissible system weight	130 kg
Reach	492 mm
Seat angle	75.5 °
Seat tube	500 mm
Shifting name	10-Gang SHIMANO "Cues"
Shifting type	derailleur shifting
Stack	648 mm
Steering tube	125 mm
Steering tube angle	65.0 °
Stem length	35.0 mm
Support	up to 25km/h
Toptube	645 mm
Trailer Approval	no
Transmission	1x 10-speed
Travel	160 mm
Type	full suspension
Wheel distance	1272 mm
Wheel size	29 "

More product images



