



## Rotary 2-post lift "SPO-Serie"

"SPOA3TS-5-EH2", incl. 2nd Operating Unit "CONTROL - SPOA3TC-NC" Load capacity: 3500 kg, total height: 4170 mm, Structure: asymmetrical, Operation: electric

### Technical data:

Lifting height: 1957 mm

Lifting time: 30 s

Column spacing: 2544 mm

Drive-through width: 2336 mm

Total width: 3000 mm

Drive power: 4.0 kW

Drive voltage: 400 V / 50 Hz

Total height EH 2: 4170 mm

Cut-off height EH 2: 4026 mm

Support arm length front min. / max.: 857 / 1143 mm

Support arm length hi. min. / max.: 876 / 1474 mm

Turntable height min. / max.: 100 / 160 mm

**Price: €3,349.95**

### Basic Data

Supplier Article Number:	SPOA3TS-EH2-EV
MSRP:	€9,768.75
SB-Article	No
Brand/Supplier	Rotary
Unit of measure:	PIECE

### Technical Data

Design	lift
Drive	electrohydraulic
Drive power	4.0 kW
Drive voltage	400.0 V
Features	without base frame

<b>Height</b>	417.0 cm
<b>Load</b>	3500.0 kg
<b>Main colour</b>	silver
<b>Max. lifting</b>	195.7 cm
<b>Type</b>	2-post lift
<b>Variant</b>	Article
<b>Width</b>	300.0 cm

**More product images**

