

VICTORIA Electric trekking bike "Manoc 6" (#1)

diamond, 28", stardust silver matt, 1x11-speed SHIMANO "Deore XT"/"Deore SLX", 54 cm / M

RRP: €4,699.00

The top-of-the-line derailleur model in the MANOC Premium Trekking Series is the ideal companion for long-distance tours.The smart Bosch system, featuring the “Performance CX” drive and the high-capacity “PowerTube 750” battery, delivers the absolute best performance currently available. Additional information not displayed on the “Kiox 300” color display can be transmitted to your smartphone via the eFlow Bike app. Other apps, such as Komoot or Strava, then use this information for navigation and route planning.The air-sprung fork, with its 80 mm of travel, offers plenty of comfort and absorbs the shocks that the wide, low-rolling-resistance tires transmit from road irregularities.The eleven gears come from a Shimano “Deore XT” Rear Derailleur. Both the derailleur and the chain and cassette are from the Linkglide series and are about three times as wear-resistant and smooth-running as a comparable standard Hyperglide version.As with all new Victoria models, the battery integrated into the down tube can be removed from the top, eliminating the need to support it as you would when removing it from the bottom. However, given the large capacity and the associated battery weight, we recommend charging it on the MANOC instead, as it’s simply more convenient.With a gross vehicle weight of 170 kg, the MANOC 6 is the ideal touring companion and, thanks to the MIK luggage rack system, can securely attach panniers and other gear without them shifting while riding.

Basic Data

Supplier Article Number:	BK25HV0510
EAN	4251971170865
MSRP:	€4,699.00
WEEE registration number	DE92509320
DST-Code	1B01
SB-Article	No
Bidex-Code	122010
Fedas-Code	155021
Brand/Supplier	VICTORIA
Unit of measure:	PIECE
Weight	28.8 kg

Technical Data

Battery capacity	750.0 Wh
Bosch Smart System	yes
Brake system	hydraulic disc brake
Child Seat Approval	no
Colour designation	stardust silver matt

Drive	chain
Drive system	BOSCH Performance Line CX
Drive version	middle motor
E-bike	yes
Engine power	250 W
Features	chain guard , electronic sliding aid , fender , frame lock , suspension fork
Frame height	54 cm
Frame shape	diamond
Frame size	M
Gears	11-speed
Gender	gents
Main colour	silver
Material	aluminium
Model range	Manoc
Permissible system weight	170 kg
Secondary colour	grey
Shifting name	1x11-Gang SHIMANO "Deore XT"/"Deore SLX"
Shifting type	derailleur shifting
Support	up to 25km/h
Torque	85 Nm
Trailer Approval	no
Transmission	1x 11-speed
Travel	80 mm
Type	trekking bike
Wheel size	28 "

Specifications

Battery	BOSCH "Powertube 750", Lithium-Ionen mit BMS, 750 Wh
Bottom bracket	BOSCH
Brake	TEKTRO "HD-T390"
Brake lever	TEKTRO "HD-T390"
Chain / belt	SHIMANO "CN-LG500"
Chain guard	HESLING "Velo" Bosch Gen.4 schwarz matt
Chain ring / pulley	FSA, 38 Z.
Charger	BOSCH 4 Ah
Crank	FSA "CK-745", Gen.4
Derailleur hanger	Slider Dropout
Display	BOSCH "Kiox 300"
Engine	BOSCH "Performance CX", 36 V, 250 W
Fender	CURANA "Apollo", 60mm, schwarz matt, Spoiler
Fork	RST 2022 "VIVair E-15 TNL", 700Cx300 mm, tapered, ohne Gewinde, 80 mm Federweg, PM-Disc, QPQ, Schutzblechaufnahme, schwarz matt

Frame	Bosch-Intube-Frame, Aluminium 6061
Frame Lock	CONTEC "Powerloc" M
Front hub	SHIMANO "HB-TC500", 15x100 mm
Front light	CONTEC "Dlux 120 E+" 120 Lux
Front rotor	TEKTRO "TR180-45", 180mm, Center-Lock
Front tire	CONTINENTAL "Contact Plus" 50-622
Grips	CONTEC "Merge Trekking Ergo"
Handlebar	ERGOTEC " Rise Bar 50 Comfort", 720 mm, Ø 31,8 mm, schwarz, Level 6
Pedals	UNION "SP-828", Alu, Antislip
Rear carrier	MASSLOAD ALU-GEPÄCKTRÄGER MIK-System
Rear derailleur	SHIMANO "Deore XT RD-M8130-SGS", 11-fach
Rear hub	SHIMANO FH-MT400-B,, 12x148 mm
Rear light	CONTEC „TL-335 E-Stop“, mit Stoplicht
Rear rotor	TEKTRO "TR180-45", 160mm, Center-Lock
Rear tire	CONTINENTAL "Contact Plus" 50-622
Remote	BOSCH "BRC3600"
Rims	MACH "650 Disc"
Saddle	SELLE ROYAL "Orbis" Moderate
Seatpost	ERGOTEC Hook, 31.6mm, 400mm, Level 6
Sensor	Pedal pressure measuring im Motor + speed sensor
Shifting lever	SHIMANO "Deore XT SL-M8130"
Spokes	Niro, 2 mm, schwarz
Sprocket / pulley	SHIMANO "CS-LG700-11 " 11-50 Z. silber
Stands	URSUS "King2", Hinterbau, 40 mm, verstellbar
Stem	ERGOTEC "Swell-R Ahead 70", Ø31,8 mm, 45 °, schwarz 120mm + 5mm Spacer

More product images

