

CONWAY Electric SUV "Xyron SUV 4.0" (#2)

full suspension, 29", metallicgrey matt, 12-speed SHIMANO "Deore", 42 cm / M

RRP: €4,999.95

Enjoy an active ride without sacrificing comfort—that's exactly what the "Xyron SUV 4.0" was built for. The full suspension system, with 150 mm of travel at both the front and rear, ensures a smooth ride over asphalt, forest trails, and rougher terrain. The geometry puts you in an active yet ergonomically balancedriding position: You sit slightly leaned forward, with direct control over the Handlebar and an efficient pedaling stroke.The Bosch mid-drive motor with an 800 Wh Battery delivers powerful assistance up to 25 km/h. The Shimano "Deore" 12-speed drivetrain offers precise shifting, while the hydraulic disc brakes ensure reliable stopping power. The combination of a short Stem, a flat steering angle, and a long wheelbase ensures confident handling—even at speed or when carrying luggage.With fenders, clever frame integration, and features like the HTM 2.0 front rack mount, BCM module, and Range Extender readiness, you're equipped for anything—from your daily commute to weekend tours.

Basic Data

Supplier Article Number:	BK26HA1060
EAN	4251971176188
MSRP:	€4,999.95
WEEE registration number	DE92509320
Fedas-Code	154020
Bidex-Code	121010
DST-Code	1E01
SB-Article	No
Brand/Supplier	CONWAY
Unit of measure:	PIECE
Weight	29.2 kg

Technical Data

Battery capacity	800.0 Wh
Bosch Smart System	yes
Brake system	hydraulic disc brake
Child Seat Approval	no
Colour designation	metallicgrey matt
Drive	chain

Drive system	BOSCH Performance Line CX
Drive version	middle motor
E-bike	yes
Engine power	250 W
Features	damper , electronic sliding aid , fender , suspension fork
Frame height	42 cm
Frame shape	full suspension
Frame size	M
Frame travel	150 mm
Gears	12-speed
Gender	gents
Main colour	grey
Material	aluminium
Model range	Xyron
Permissible system weight	140 kg
Shifting name	12-Gang SHIMANO "Deore"
Shifting type	derailleur shifting
Support	up to 25km/h
Trailer Approval	no
Transmission	1x 12-speed
Travel	150 mm
Type	SUV
Wheel size	29 "

Specifications

Battery	BOSCH "Powertube 800", Lithium-Ionen mit BMS, HOR w. SOP Pivot
Bottom bracket	BOSCH
Brake	TEKTRO "HD-M535", 4/4-Kolben
Brake lever	TEKTRO "HD-M535"
Chain / belt	SHIMANO "CN-M6100"
Chain ring / pulley	MIRANDA "36T w Guard"
Charger	Bosch 4 A, BES3
Crank	MIRANDA "Virage", Q12, 165mm
Damper	FOX "Float Rhythm", 2 Pos.
Derailleur hanger	0347028/3
Display	BOSCH "Kiox 300"
Engine	BOSCH Mittelmotor Gen.5 "Performance CX", 36 V, 250 W
Fender	CURANA "Apollo 75"
Fork	ROCKSHOX "Recon RL", 150 mm
Frame	CONWAY Fully Intube Bosch, Alu
Front hub	SHIMANO "HB-TC500", 15 x 110 mm
Front light	HERRMANS "MR9"

Front rotor	TEKTRO "TR203-45", 203 mm
Front tire	SCHWALBE "Marathon Plus MTB"", 57-622
Grips	SQLAB "70X"
Handlebar	LEVEL 9 "Low Riser", 31,8, 720 mm
Headset	ACROS "ZS56-ZS56", Blocklock
Pedals	VP "VPE-527"
Rear carrier	MASSLOAD "MIK", inkl. Federklappe
Rear derailleur	SHIMANO "Deore", 12speed
Rear hub	SHIMANO "FH-TC500", 12 x 148mm
Rear light	AXA "Juno E-Bike", Brake Light
Rear rotor	TEKTRO "TR203-45", 203 mm
Rear tire	SCHWALBE "Marathon Plus MTB"", 57-622
Remote	BOSCH "Mini Remote"
Rims	CONWAY "TRYP 30"
Saddle	SELLE ROYAL "SRX+", 145mm
Seatpost	LIMOTEC "D1", 31,6 mm, 150 mm
Sensor	Pedal pressure measuring im Motor + speed sensor
Shifting lever	SHIMANO "Deore SL-M6100"
Spokes	Niro
Sprocket / pulley	SHIMANO "Deore", 10-51 Z.
Stands	HEBIE "0650 M Abstellheld IC"
Stem	LEVEL 9 "Adjustable", 65 mm
System Interface	BOSCH "BRC3100"

More product images





