

QiO Electric compact bike "Compact CX5x" (#1)

unisex, 20", retro blue matt, Shimano Nexus 5-speed, 48 cm

RRP: €4,999.00

Suspension meets functionality—the "Compact CX5x" from QiO combines the advantages of a compact e-bike with the comfort of a Suspension Fork. With 80 mm of travel, it smoothly absorbs bumps and delivers noticeably greater riding comfort—especially on cobblestones, forest trails, or rough bike paths. This makes every ride more relaxing, no matter where you're headed. With a high battery capacity of a whopping 800 Wh, your rides can easily extend into the evening hours. The Bosch mid-drive motor with Smart System provides powerful assistance up to 25 km/h, while the low-maintenance belt drive and the 5-speed Shimano "Nexus" hub gear system ensure a smooth, reliable riding experience. The hydraulic 4-piston disc brakes from Magura bring you to a safe stop—in any weather.Hydraulic 4-piston disc brakes ensure maximum safety and control, providing reliable stopping power even in wet conditions and at high speeds. Lighting is provided by the high-quality Busch+Müller IQ-XS Beam LED Front Light, which offers excellent illumination of the road with 100 lux low beam and 150 lux high beam—ideal for riding in the dark and in poor visibility conditions.

Basic Data

EAN	4251971178427
MSRP:	€4,999.00
Fedas-Code	159021
DST-Code	1A01
WEEE registration number	DE92509320
SB-Article	No
Bidex-Code	123040
Brand/Supplier	QiO
Unit of measure:	PIECE
Weight	28.6 kg

Technical Data

Battery capacity	800.0 Wh
Bosch Smart System	yes
Brake system	hydraulic disc brake
Colour designation	retro blue matt
Drive	belt
Drive system	BOSCH Performance Line CX
Drive version	middle motor
E-bike	yes
Engine power	250 W

Features	chain guard , electronic sliding aid , fender , suspension fork , system carrier
Frame height	48 cm
Frame shape	unisex
Gears	5-speed
Gender	unisex
Main colour	blue
Material	aluminium
Model range	Compact
Permissible system weight	180 kg
Shifting name	Shimano Nexus 5-Gang
Shifting type	internal gear shifting
Support	up to 25km/h
Travel	80 mm
Type	compact bike
Wheel size	20 "

Specifications

Battery	BOSCH "Active Line Plus", max. 50 Nm
Battery Lock	ABUS "XPlus"
Bottom bracket	BOSCH
Chain / belt	GATES "CDX"
Chain guard	SKS "Chainblade"
Chain ring / pulley	Gates "CDX Fin Line", 46 teeth, belt line 45.5 mm
Charger	BOSCH 4 A
Crank	PROWHEEL "EB03", 170 mm
Derailleur hanger	Slider dropout, suitable for P5, PX5+
Display	BOSCH "Kiox 500", 4-stages, Remote Control, push-aid
Engine	BOSCH "Performance Line CX", BDU38, max. 100 Nm
Fender	SKS "A 69 R"
Fork	SR SUNTOUR "SF22-Mobie34-CGO-Boost", 80 mm travel, Thru Axle
Frame	QIO Compact, Bosch Gen. 4, BES3, aluminum, 48 cm
Front brake	MAGURA "LOUISE"
Front hub	SHIMANO "HB-TC500-15-B", 15 x 110 mm Boost, Center Lock, Thru Axle
Front light	Busch + Müller "IQ-XS E Highbeam", 100 Lux
Front rotor	MAGURA "MDR-C", Ø 180 mm
Front tire	MAXXIS "MetroPass AT", 62-406, Reflex
Grips	HERRMANS "Nucore Town", wave
Handlebar	ergotec "Lady Town", 620 mm, Ø 31.8 mm, 30° backsweep
Headset	ACROS ZS66/31.75 OD74 / ZS66/46/OD72, blocklock
Pedals	MARWI "SP-157" Faltpedale
Rear brake	MAGURA "LOUISE"
Rear carrier	"MIK HD 2.0" for MIK Side

Rear hub	SHIMANO "Nexus SG-C7000-5D", 5-speed, Center Lock
Rear light	Busch + Müller "Dart E Brex "
Rear rotor	MAGURA "MDR-C", Ø 180 mm
Rear tire	MAXXIS "MetroPass AT", 62-406, Reflex
Rims	DT SWISS "U 663", 36 hole, eyeletted, tubeless ready
Saddle	Selle Royal "On", Moderate Wide
Seatpost	by,schulz "G.2 ST", Ø 34.9 mm, 400 mm long, 30 mm travel, 12 mm offset
Sensor	Pedal pressure measuring im Motor + speed sensor
Shifting lever	SHIMANO "Nexus SL-C7000-5"
Spokes	2,0 mm, Niro, schwarz
Sprocket / pulley	Gates "CDX:BLACK Fin Line", 28 teeth
Stands	URSUS "Invisible Mount", 20"
Stem	ergotec "Sepia Ahead XL", 80 mm long, adjustable, level 5

More product images

