

QiO Electric compact bike "Compact P5" (#1)

unisex, 20", imola red, Shimano Nexus 5-speed idle, 48 cm

RRP: €3,799.00

The QiO "Compact P5" is your smart companion for everyday life—compact, powerful, and stylish. With the Bosch mid-drive motor, Smart System, and 545 Wh Battery, you can fully enjoy dynamic assistance up to 25 km/h. The low-maintenance belt drive and the 5-speed Shimano “Nexus” hub gear system ensure a quiet, smooth ride—ideal for both city riding and touring.The 20-inch wheels and sturdy aluminum frame offer agility and comfort. The low step-through makes it easy to get on and off the bike.Hydraulic disc brakes, fenders, and a maximum weight capacity of 180 kg make the QiO “Compact P5” a true everyday hero. Everything fits perfectly—for you and your active lifestyle.

Basic Data

EAN	4251971177932
MSRP:	€3,799.00
Fedas-Code	159021
DST-Code	1A01
WEEE registration number	DE92509320
SB-Article	No
Bidex-Code	123040
Brand/Supplier	QiO
Unit of measure:	PIECE
Weight	24.8 kg

Technical Data

Battery capacity	545.0 Wh
Bosch Smart System	yes
Brake system	hydraulic disc brake
Colour designation	imola red
Drive	belt
Drive system	BOSCH Performance Line
Drive version	middle motor
E-bike	yes
Engine power	250 W
Features	chain guard , electronic sliding aid , fender , system carrier
Frame height	48 cm

Frame shape	unisex
Gears	5-speed
Gender	unisex
Main colour	red
Material	aluminium
Model range	Compact
Permissible system weight	180 kg
Shifting name	5-Gang SHIMANO "Nexus" Leerlauf
Shifting type	internal gear shifting
Support	up to 25km/h
Type	compact bike
Wheel size	20 "

Specifications

Battery	BOSCH "PowerPack 545", 545 Wh
Battery Lock	ABUS Battery Lock
Bottom bracket	BOSCH
Chain guard	SKS "Chainblade"
Chain ring / pulley	Gates "CDC Fin Line", 46 teeth, belt line 45.5 mm
Charger	BOSCH 4 A
Crank	PROWHEEL "EB03", 170 mm
Derailleur hanger	Slider dropout, suitable for P5, PX5+
Display	BOSCH "Purion 200" Display, 4-stage, Remote Control, Pushing Help
Engine	BOSCH "Performance Line" engine, max. 75 Nm
Fender	SKS "A 69 R"
Fork	Aluminum, tapered 1 1/4" - 1.5"
Frame	QIO Compact, Bosch Gen. 4, BES3, aluminum, 48 cm
Front brake	MAGURA "MT A2"
Front hub	SHIMANO "HB-TC500," 12 x 100 mm, Center Lock, Thru Axle
Front light	Busch + Müller "Briq-S E", 60 lux
Front rotor	MAGURA "MDR-A", Ø 180 mm
Front tire	CONTINENTAL "eContact Plus," 62-406, Reflex
Grips	HERRMANS "Clik Original DD37"
Handlebar	ergotec "Lady Town", 620 mm, Ø 31.8 mm, 30° backsweep
Headset	ACROS ZS66/31.75 OD74 / ZS66/46/OD72, blocklock
Pedals	MARWI "SP-157" Faltpedale
Rear brake	MAGURA "MT A2"
Rear carrier	"MIK HD 2.0" for MIK Side
Rear hub	SHIMANO "Nexus SG-C7000-5D", 5-speed, Center Lock
Rear light	Busch + Müller "Dart E Brex "
Rear rotor	MAGURA "MDR-A", Ø 180 mm
Rear tire	CONTINENTAL "eContact Plus," 62-406, Reflex

Rims	DT SWISS "U 663", 36 hole, eyeletted, tubeless ready
Saddle	Selle Royal "On", Moderate Wide
Seatpost	by,schulz "R.3 P-QR", Ø 34.9 mm, 400 mm long, 25 mm offset
Sensor	Pedal pressure measuring im Motor + speed sensor
Shifting lever	SHIMANO "Nexus SL-C7000-5"
Spokes	2,0 mm, Niro, schwarz
Sprocket / pulley	Gates "CDX:BLACK Fin Line", 28 teeth
Stands	URSUS "Invisible Mount", 20"
Stem	ergotec "Sepia Ahead XL", 80 mm long, adjustable, level 5

More product images

