

QiO Electric compact bike "Compact PX5+" (#1)

unisex, 20", dark olive matt, 5-speed SHIMANO "Nexus" neutral gear, 48 cm

RRP: €4,799.00

Compact, powerful, stylish—the "Compact PX5+" from QiO is your smart companion for urban mobility. With the Bosch mid-drive motor and the Bosch Smart System, you'll enjoy reliable assistance up to 25 km/h—quiet, efficient, and low-maintenance thanks to the belt drive. The 800 Wh battery keeps you going all day long, even on longer rides.The 5-speed Shimano "Nexus" hub gear system ensures smooth shifting, while the hydraulic disc brakes give you full control at all times. With 20" wheels, a suspension Seatpost, and a sturdy aluminum frame, this compact bike is designed for everyone—regardless of age or riding style.The "+" stands for a maximum rider weight of 150 kg—ideal for heavier riders or carrying extra cargo. This not only makes your everyday life easier but also significantly more flexible—and all with style.

Basic Data

EAN	4251971178151
MSRP:	€4,799.00
Fedas-Code	159021
DST-Code	1A01
WEEE registration number	DE92509320
SB-Article	No
Bidex-Code	123040
Brand/Supplier	QiO
Unit of measure:	PIECE
Weight	27.5 kg

Technical Data

Battery capacity	800.0 Wh
Bosch Smart System	yes
Brake system	hydraulic disc brake
Colour designation	dark olive matt
Drive	belt
Drive system	BOSCH Performance Line PX
Drive version	middle motor
E-bike	yes
Engine power	250 W
Features	chain guard , electronic sliding aid , fender , system carrier
Frame height	48 cm

Frame shape	unisex
Gears	5-speed
Gender	unisex
Main colour	green
Material	aluminium
Model range	Compact
Permissible system weight	180 kg
Shifting name	5-Gang SHIMANO "Nexus" Leerlauf
Shifting type	internal gear shifting
Support	up to 25km/h
Type	compact bike
Wheel size	20 "

Specifications

Battery	BOSCH "Active Line Plus", max. 50 Nm
Battery Lock	ABUS "XPlus"
Bottom bracket	BOSCH
Chain / belt	GATES "CDX"
Chain guard	SKS "Chainblade"
Chain ring / pulley	Gates "CDX Fin Line", 46 teeth, belt line 45.5 mm
Charger	BOSCH 4 A
Crank	PROWHEEL "EB03", 170 mm
Derailleur hanger	Slider dropout, suitable for P5, PX5+
Display	BOSCH "Kiox 300", 4-stages, remote control, push aid
Engine	BOSCH "Performance Line PX", max. 85 Nm
Fender	SKS "A 69 R"
Fork	Aluminum, tapered 1 1/4" - 1.5"
Frame	QIO Compact, Bosch Gen. 4, BES3, aluminum, 48 cm
Front brake	MAGURA "LOUISE"
Front hub	SHIMANO "HB-TC500," 12 x 100 mm, Center Lock, Thru Axle
Front light	Busch + Müller "Briq-S E", 60 lux
Front rotor	MAGURA "MDR-C", Ø 180 mm
Front tire	SCHWALBE "Pick-up", 60-406, Reflex
Grips	HERRMANS "Nucore Town", wave
Handlebar	ergotec "Lady Town", 620 mm, Ø 31.8 mm, 30° backsweep
Headset	ACROS ZS66/31.75 OD74 / ZS66/46/OD72, blocklock
Pedals	MARWI "SP-157 HD" Faltpedale
Rear brake	MAGURA "LOUISE"
Rear carrier	"MIK HD 2.0" for MIK Side
Rear hub	SHIMANO "Nexus SG-C7000-5D", 5-speed, Center Lock
Rear light	Busch + Müller "Dart E Brex "
Rear rotor	MAGURA "MDR-C", Ø 180 mm

Rear tire	SCHWALBE "Pick-up", 60-406, Reflex
Rims	DT SWISS "U 663", 36 hole, eyeletted, tubeless ready
Saddle	Selle Royal "On", Moderate Wide
Seatpost	by,schulz "G.2 ST", Ø 34.9 mm, 400 mm long, 30 mm travel, 12 mm offset
Sensor	Pedal pressure measuring im Motor + speed sensor
Shifting lever	SHIMANO "Nexus SL-C7000-5"
Spokes	2,0 mm, Niro, schwarz
Sprocket / pulley	Gates "CDX:BLACK Fin Line", 28 teeth
Stands	URSUS "Invisible Mount", 20"
Stem	ergotec "SWELL-RE", 80 mm long, adjustable, level 6

More product images

