

QiO Electric compact bike "Compact AP-8" (#1)

unisex, 20", lunar white matt, 8-speed SHIMANO "Nexus" neutral gear, 48 cm

RRP: €3,299.00

The "Compact AP-8" from QiO is the ideal entry-level model for anyone who wants to combine compact mobility with style and functionality. With 20" wheels and a sturdy aluminum frame, it offers you maneuverability and a compact size perfect for urban living.The Bosch mid-drive motor with Smart System provides reliable assistance up to 25 km/h. The 8-speed Shimano “Nexus” hub gear system ensures smooth, precise shifting, while the chain drive gives you a direct riding feel. Hydraulic disc brakes bring you to a safe stop—even in wet conditions.With a 545 Wh battery capacity, Fenders, A Rear Light with Brake Light, and a maximum gross weight of 180 kg, the “Compact AP-8” is a well-designed compact bike for anyone looking for a compact e-bike that’s easy to handle.

Basic Data

EAN	4251971178687
MSRP:	€3,299.00
Fedas-Code	159021
DST-Code	1A01
WEEE registration number	DE92509320
SB-Article	No
Bidex-Code	123040
Brand/Supplier	QiO
Unit of measure:	PIECE
Weight	26.6 kg

Technical Data

Battery capacity	545.0 Wh
Bosch Smart System	yes
Brake system	hydraulic disc brake
Colour designation	lunar white matt
Drive	chain
Drive system	BOSCH Active Line Plus
Drive version	middle motor
E-bike	yes
Engine power	250 W
Features	chain guard , deep entry , electronic sliding aid , fender , system carrier
Frame height	48 cm

Frame shape	unisex
Gears	8-speed
Gender	unisex
Main colour	white
Material	aluminium
Model range	Compact
Permissible system weight	180 kg
Shifting name	8-Gang SHIMANO "Nexus" Leerlauf
Shifting type	internal gear shifting
Support	up to 25km/h
Type	compact bike
Wheel size	20 "

Specifications

Battery	BOSCH "PowerPack 545", 545 Wh
Battery Lock	ABUS Battery Lock
Bottom bracket	BOSCH
Brake lever	TRP HD-EU817
Chain / belt	KMC "e1 EPT"
Chain guard	hebie "Chainglider", front 44 teeth, rear 16-18 teeth
Chain ring / pulley	STRONGLIGHT, 44 teeth
Charger	BOSCH 2 A
Crank	Stronglight "Magan 3B", 170 mm
Derailleur hanger	QIO Slider Dropout
Display	BOSCH "Purion 200" Display, 4-stage, Remote Control, Pushing Help
Engine	BOSCH "Active Line Plus", max. 50 Nm
Fender	SKS "A 69 R"
Fork	Aluminum, tapered 1 1/4" - 1.5"
Frame	QIO Compact, Bosch Gen. 3, BES3, aluminum, 48 cm
Front brake	TRP "C1.8 HD-EU817", Post Mount
Front hub	SHIMANO "HB-QC400," Center Lock, QR
Front light	CONTEC "DLUX 50 E+", 50 lux
Front rotor	TRP "TR-25", Ø 180 mm, Centerlock
Front tire	CONTINENTAL "eContact Plus," 62-406, Reflex
Grips	HERRMANS "Clik Original DD37"
Handlebar	ergotec "Lady Town", 620 mm, Ø 31.8 mm, 30° backsweep
Headset	TOKEN "TK255E-HJ04", IS52/40 / IS52/44
Pedals	UNION "SP-153" Faltpedal
Rear brake	TRP "C1.8 HD-EU817"
Rear carrier	"MIK HD 2.0" for MIK Side
Rear hub	SHIMANO "Nexus SG-C6061-8D", 8-speed, Center Lock
Rear light	CONTEC "TL-335 E-Stop", stop light

Rear rotor	TEKTRO "TR180-35", Ø 180 mm, Center Lock
Rear tire	CONTINENTAL "eContact Plus," 62-406, Reflex
Rims	SCHÜRMANN "YAK DISC 25", 25-406, 36 holes, disc brake, black
Saddle	Selle Royal "On", Moderate Wide
Seatpost	by,schulz "R.3 P-QR", Ø 34.9 mm, 400 mm long, 25 mm offset
Sensor	Pedal pressure measuring im Motor + speed sensor
Shifting lever	SHIMANO "Nexus, SL-C6000-8"
Spokes	2mm, schwarz
Sprocket / pulley	SHIMANO "SM-GEAR", 16 teeth
Stands	URSUS "R78 - King Mini"
Stem	BY.SCHULZ "Stem SDS", 1 1/8", 31.8 mm handlebar clamps, 70 mm long, angle 7°, black

More product images

