

# CONWAY Electric MTB full suspension "Xyron ST 10.0" (#2)

**full suspension, 29", light grey matt / black matt, 12-Speed SHIMANO "XT Di2" Mix, 46 cm / XL**

## RRP: €5,999.95

Want a bike that can handle anything—and looks great doing it? The "Xyron ST 10.0" is our top model in the ST series, and with its Bosch mid-drive motor and 800 Wh Battery, it'll easily take you through long rides and steep climbs. The combination of 150 mm of suspension travel, 29-inch wheels, and a lightweight carbon frame ensures solid traction and precise handling.Thanks to the new electronic Shimano XT Di2 shifting system, you'll now enjoy an even better riding experience: with features like "Auto Shift" and "Free Shift," you can focus entirely on the trail while the shifting system takes care of the rest! And should you ever take a hard fall, the Impact Recovery feature even protects your Rear Derailleur.The sporty geometry positions you centrally over the bike and puts plenty of pressure on the Front Wheel—giving you maximum control on technical or steep terrain. And best of all: the handling remains super agile even on the roughest terrain. And with the tool mount under the top tube and the hidden kickstand mount on the rear triangle, you'll be well-equipped even off the trail!

### Basic Data

| | |
|---|---|
| **Supplier Article Number:** | BK26HA1340 |
| **EAN** | 4251971182455 |
| **MSRP:** | €5,999.95 |
| **Fedas-Code** | 154050 |
| **WEEE registration number** | DE92509320 |
| **DST-Code** | 1E01 |
| **SB-Article** | No |
| **Bidex-Code** | 121020 |
| **Brand/Supplier** | CONWAY |
| **Unit of measure:** | PIECE |
| **Weight** | 23.4 kg |

### Technical Data

| | |
|---|---|
| **Battery capacity** | 800.0 Wh |
| **Brake system** | hydraulic disc brake |
| **Category E-bike** | 3 |
| **Child Seat Approval** | no |
| **Colour designation** | light grey matt / black matt |
| **Drive** | chain |

| | |
|---|---|
| **Drive system** | BOSCH Performance Line CX |
| **Drive version** | middle motor |
| **E-bike** | yes |
| **Engine power** | 250 W |
| **Features** | damper , electronic sliding aid , suspension fork |
| **Frame height** | 46 cm |
| **Frame shape** | full suspension |
| **Frame size** | XL |
| **Frame travel** | 150 mm |
| **Gears** | 12-speed |
| **Gender** | gents |
| **Main colour** | grey |
| **Material** | carbon |
| **Model range** | Xyron |
| **Permissible system weight** | 140 kg |
| **Secondary colour** | black |
| **Shifting name** | 12-Gang SHIMANO "XT Di2" Mix |
| **Shifting type** | derailleur shifting |
| **Support** | up to 25km/h |
| **Trailer Approval** | no |
| **Transmission** | 1x 12-speed |
| **Travel** | 150 mm |
| **Type** | full suspension |
| **Wheel size** | 29 " |

## Specifications

| | |
|---|---|
| **Battery** | BOSCH "Powertube 800", Lithium-Ionen mit BMS, HOR w. SOP Pivot |
| **Bottom bracket** | BOSCH |
| **Brake** | TEKTRO "SLATE EVO HD-M807", 4/4-Kolben |
| **Brake lever** | TEKTRO "SLATE EVO HD-M807" |
| **Chain / belt** | SHIMANO "Deore" |
| **Chain ring / pulley** | E13 "Helix Core e*spec", 34 Z. |
| **Charger** | Bosch 4 A, BES3 |
| **Crank** | E13 "Helix Core e*spec", 160 mm |
| **Damper** | FOX "Float Rhythm", 2 Pos. |
| **Derailleur hanger** | 0347028/3 |
| **Display** | BOSCH "Kiox 400" |
| **Engine** | BOSCH Mittelmotor Gen.5 "Performance CX", 36 V, 250 W |
| **Fork** | FOX "36 Performance" |
| **Frame** | CONWAY Fully Intube Bosch, Carbon |
| **Front hub** | NEWMEN "Basic", 15 x 110 mm |
| **Front rotor** | TEKTRO "RS01E", 203 mm |

| | |
|---|---|
| **Front tire** | SCHWALBE "Albert Trail Pro" 63-622, ultra soft, Radial |
| **Grips** | SQLAB "70X" |
| **Handlebar** | LEVEL 9 "Race e35.0", Rise 20mm, 780 mm |
| **Headset** | ACROS "ZS56-ZS56", Blocklock |
| **Rear derailleur** | SHIMANO "Deore XT RD-M8260 Di2", 12speed |
| **Rear hub** | NEWMEN "Basic", 12 x 148 mm, MS |
| **Rear rotor** | TEKTRO "RS01E", 203 mm |
| **Rear tire** | SCHWALBE "Albert Trail Pro" 63-622, soft, Radial |
| **Remote** | BOSCH "Mini Remote" |
| **Rims** | NEWMEN "Performance 30 Base", 30-622 |
| **Saddle** | SELLE ROYAL "SRX+", 145mm |
| **Seatpost** | LIMOTEC "A1", 31,6 mm, 170 mm |
| **Sensor** | Pedal pressure measuring im Motor + speed sensor |
| **Shifting lever** | SHIMANO "Deore XT Di2 Shift Switch" |
| **Spokes** | SAPIM |
| **Sprocket / pulley** | SHIMANO "Deore", 10-51 Z. |
| **Stem** | LEVEL 9 "Race e35.0", 50mm |