



CONWAY Electric MTB hardtail "Cairon S 1.0" (#1)

diamond, 27,5", black matt / light grey matt, 9-speed SHIMANO "Cues", 41 cm / S

RRP €2,699.95

The Cairon S 1.0 gives you a powerful, comfortable and safe start to e-mobility. The balanced geometry ensures stable handling and an active riding position - ideal for relaxed tours on forest trails, gravel tracks or through the city. The combination of 29" wheels (depending on the frame size) and 120 mm travel on the RST Fork ensures that you can roll over obstacles with confidence. The Bosch Performance CX Gen. 4 engine provides you with reliable support, complemented by an integrated 625 Wh Battery and the smart Bosch Kiox 300 Display for full control on the go. The Shimano 9-speed derailleur ensures precise gear changes, while 180 mm hydraulic Disc Brakes guarantee safe braking performance at all times. Robust Schwalbe Tough Tom tires offer you grip and stability on any surface. Thanks to the high-quality aluminum frame and the well thought-out equipment, the Cairon S 1.0 is a reliable partner - whether for the daily commute to work, spontaneous excursions or sporty weekend tours.

Basic Data

EAN	4251971183759
MSRP:	€2,699.95
WEEE registration number	DE92509320
Fedas-Code	154020
Bidex-Code	121010
DST-Code	1E01
SB-Article	No
Brand/Supplier	CONWAY
Unit of measure:	PIECE
Weight	24.9 kg

Technical Data

Battery capacity	625.0 Wh
Brake system	hydraulic disc brake
Category E-bike	3
Chainstay	440 mm
Child Seat Approval	no
Colour designation	black matt / light grey matt
Drive	chain

Drive system	BOSCH Performance Line CX
Drive version	middle motor
E-bike	yes
Engine power	250 W
Features	electronic sliding aid , suspension fork
Frame height	41 cm
Frame shape	diamond
Frame size	S
Gears	9-speed
Gender	gents
Main colour	black
Material 1	aluminium
Model range	Cairon
Permissible system weight	130 kg
Reach	401 mm
Seat angle	74.5 °
Seat tube	410 mm
Secondary colour	grey
Shifting name	9-Gang SHIMANO "Cues"
Shifting type	derailleur shifting
Stack	619 mm
Steering tube	130 mm
Steering tube angle	67.0 °
Stem length	75.0 mm
Support	up to 25km/h
Toptube	575 mm
Trailer Approval	no
Transmission	1x 9-speed
Travel	120 mm
Type	hardtail
Wheel distance	1135 mm
Wheel size	27,5 "

More product images

