

CONTEC Aluminium Rim "Xeta" 28 / 29"

27-622, 605 mm ERD (measured including spoke holes), 18 mm high, 27 mm inner width, 31 mm outer width, approx. 578 g

RRP: €39.95

The ideal foundation for building a tubeless-ready wheel for 29" bikes with 32 spokes. Thanks to its hollow-chamber construction, the Xeta Max aluminium rim, made of 6063 aluminum, is particularly lightweight and sturdy. When assembled into a complete wheel, these rims are suitable for a system weight of up to 150 kg. With an inner rim width of 27 mm, tires ranging from 53 to 69 mm in width fit on the rim. The single-eyelet spoke holes ensure additional durability of the aluminium rim by reducing friction between the Spoke Nipples and the rim and also preventing the Nipples from grinding into the rim. The Xeta Max rim is only suitable for wheels with disc brakes. You can find compatible tubeless rim tape in our CONTEC product range.

Basic Data

Supplier Article Number:	30008492
MSRP:	€39.95
Bidex-Code	204010
Fedas-Code	160464
DST-Code	2P02
SB-Article	No
Brand/Supplier	CONTEC
Unit of measure:	PIECE

Technical Data

Brake compatibility rim	disc
Brake mounting	disc - 5-hole , disc - 6-hole , disc - Center Lock , drum brake , roller brake
Brake track	no
Design	doublewall
E-bike type	ready
ETRTO	27-622
For wheel	yes
Main colour	black
Number of spoke holes	32 holes
Permissible system weight	150 kg
Rim height	18 mm
Rim inner width	27 mm
Rim model	Xeta
Rim outer width	31 mm
Spoke Hole	easy eyelets
Tubeless system	tubeless ready
Valve type	Sclaverand (SV)
Variant	Article
Wheel size	28 / 29 "

More product images





