

CONTEC Aluminium Rim "Xeta"

27-622, 605 mm ERD (measured incl. spoke holes), 18 mm high, 27 mm inner width, 31 mm outer width, approx. 578 g

Price: €19.99

The ideal basis for building a tubeless-ready Wheel for 29" wheels with 32 Spokes. Thanks to the hollow chamber design, the Xeta Max rims made of 6063 aluminum are particularly light and stable. In the finished Wheel, these rims are suitable for a system weight of up to 150 kg. With an inner rim width of 27 mm, tires ranging in size from 53 to 69 mm fit on the rim. The single eyeletted nipple holes ensure additional durability of the rim by reducing the friction between the Spoke Nipple and the rim and also prevent the Nipples from working their way into the rim. The Xeta Max rim is only suitable for wheels with disc brakes. You can find suitable tubeless rim tapes in our CONTEC range.

Basic Data

| | |
|--------------------------|----------|
| Supplier Article Number: | 30008492 |
| MSRP: | €39.95 |
| Bidex-Code | 204010 |
| Fedas-Code | 160464 |
| DST-Code | 2P02 |
| SB-Article | No |
| Brand/Supplier | CONTEC |
| Unit of measure: | PIECE |

Technical Data

| | |
|---------------------------|--|
| Brake compatibility rim | disc |
| Brake mounting | disc - 5-hole , disc - 6-hole , disc - Center Lock , drum brake , roller brake |
| Brake track | no |
| Design | doublewall |
| ETRTO | 27-622 |
| For wheel | yes |
| Main colour | black |
| Number of spoke holes | 32 holes |
| Permissible system weight | 150 kg |
| Rim height | 18 mm |
| Rim outer width | 31 mm |
| Rim width | 27 mm |
| Spoke Hole | easy eyelets |
| Text wheel configurator | suitable for E-bike |
| Tubeless system | tubeless ready |
| Valve type | Sclaverand (SV) |
| Variant | Article |
| Wheel size | 28 / 29 " |