

Rotary 2-post lift "SPO-Serie"

"SPOA40AV-EH2", incl. 2nd Operating Unit "CONTROL - SPOA3TC-NC" and 8-piece set of adapter extensions "VSG.2CHYD.902917", load capacity: 4000 kg, total height: 4170 mm, superstructure: asymmetrical, operation: electric

Technical data:

Lifting height: 1950 mm

Lifting time: 30 s

Column spacing: 2829 mm

Drive-through width: 2546 mm

Total width: 3211 mm

Drive power: 4.0 kW

Drive voltage: 400 V / 50 Hz

Total height EH 2: 4230 mm

Cut-off height EH 2: 4065 mm

Support arm length front min. / max.: 470 / 1039 mm (3-fold)

Support arm length hi. min. / max.: 723 / 1478 mm (3-fold)

Turntable height min. / max.: 86 / 115 mm

RRP: 8.157,45 €

Datos maestros

Número de artículo del proveedor:	SPOA40AV-EH2
EAN	4057612975666
UVP	8.157,45 €
SB-Artículo	No
Marca/Proveedor	Rotary
Unidad de medida:	PIECE

Datos técnicos

Altura	417.0 cm
Altura de elevación máx.	195.0 cm
Anchura	349.6 cm
Artículo	Article
Características	without base frame
Carga	4000.0 kg
Categoría	2-post lift
Color principal	Plata
Potencia motriz	4.0 kW
Propulsión	electrohydraulic
Tensión de propulsión	400.0 V
Versión	lift

More product images





