



BS-BATTERY Battery "BTX4L-BS"

MTF maintenance-free, 4.2 Ah

Attach the supplied acid pack after removing the adhesive strip and allow to run evenly into all cells. Leave to stand for about 1-2 hours and then press the sealing strip on firmly. Once filled, the battery is sealed and no further maintenance is necessary.

Caution Batteries from 12 V may require recharging! Never open or drill into these sealed (MTF) batteries or remove the sealing strip!

Price: 13,14 €

Datos maestros

Número de artículo del proveedor:	300617
EAN	3661451001175
UVP	24,44 €
SB-Artículo	No
Marca/Proveedor	BS-BATTERY
Unidad de medida:	PIECE
Weight	1.407 kg

Datos técnicos

Altura	85.0 mm
Anchura	70.0 mm
Artículo	Article
Atornilladura	M5
Cantidad de llenado	0.2 l
Capacidad 10 h	4.0 Ah
Capacidad 20 h	4.2 Ah
Corriente de arranque en frío CCA (EN)	50 A
Energía	38.40 Wh
Longitud	113.0 mm
Polo negativo	front left
Polo positivo	front right
Purga de aire	internal

Tensión	12V
Versión	MTF , with acid pack
Ámbito de aplicación	motorcycle