



## BS-BATTERY Battery "BTX14 / BTX14-BS"

MTF maintenance-free

Attach the acid pack supplied after removing the adhesive strip and allow to run evenly into all cells. Leave to stand for about 1-2 hours and then press the sealing strip firmly into place. Once filled, the battery is sealed and no further maintenance is required.

Caution Batteries from 12 V may require recharging! Never open or drill into these sealed (MTF) batteries or remove the sealing strip!

**Price: 41,26 €**

### Datos maestros

Número de artículo del proveedor:	300604
EAN	3661451001045
UVP	76,71 €
SB-Artículo	No
Marca/Proveedor	BS-BATTERY
Unidad de medida:	PIECE
Weight	4.478 kg

### Datos técnicos

Altura	145.0 mm
Anchura	87.0 mm
Artículo	Article
Atornilladura	M6
Cantidad de llenado	0.7 l
Capacidad 10 h	12.0 Ah
Capacidad 20 h	12.6 Ah
Corriente de arranque en frío CCA (EN)	200 A
Energía	153.60 Wh
Longitud	150.0 mm
Polo negativo	front right
Polo positivo	front left

<b>Purga de aire</b>	internal
<b>Tensión</b>	12V
<b>Versión</b>	MTF , with acid pack
<b>Ámbito de aplicación</b>	motorcycle