



BS-BATTERY Battery "BTX12 / BTX12-BS"

MTF maintenance-free

Attach the acid pack supplied after removing the adhesive strip and allow to run evenly into all cells. Leave to stand for about 1-2 hours and then press the sealing strip on firmly. Once filled, the battery is sealed and no further maintenance is necessary.

Caution Batteries from 12 V may require recharging! Never open or drill into these sealed (MTF) batteries or remove the sealing strip!

RRP 64,10 €

Datos maestros

Número de artículo del proveedor:	300603
EAN	3661451001038
UVP	64,10 €
SB-Artículo	No
Marca/Proveedor	BS-BATTERY
Unidad de medida:	PIECE
Weight	3.576 kg

Datos técnicos

Altura	130.0 mm
Anchura	87.0 mm
Artículo	Article
Atornilladura	M6
Cantidad de llenado	0.6 l
Capacidad 10 h	10.0 Ah
Capacidad 20 h	10.5 Ah
Corriente de arranque en frío CCA (EN)	180 A
Energía	128.00 Wh
Longitud	150.0 mm
Número comparativo	BTX12-BS
Polo negativo	front right
Polo positivo	front left
Purga de aire	internal
Tensión	12V
Versión	MTF , with acid pack
Ámbito de aplicación	motorcycle