



BS-BATTERY Battery "BTX7A / BTX7A-BS"

MTF maintenance-free

Attach the acid pack supplied after removing the adhesive strip and allow to run evenly into all cells. Leave to stand for about 1-2 hours and then press the sealing strip on firmly. Once filled, the battery is sealed and no further maintenance is necessary.

Caution Batteries from 12 V may require recharging! Never open or drill into these sealed (MTF) batteries or remove the sealing strip!

RRP 41,20 €

Datos maestros

| | |
|-----------------------------------|---------------|
| Número de artículo del proveedor: | 300619 |
| EAN | 3661451001199 |
| UVP | 41,20 € |
| SB-Artículo | No |
| Marca/Proveedor | BS-BATTERY |
| Unidad de medida: | PIECE |
| Weight | 2.292 kg |

Datos técnicos

| | |
|--|-------------|
| Altura | 93.0 mm |
| Anchura | 87.0 mm |
| Artículo | Article |
| Atornilladura | M6 |
| Cantidad de llenado | 0.3 l |
| Capacidad 10 h | 6.0 Ah |
| Capacidad 20 h | 6.3 Ah |
| Corriente de arranque en frío CCA (EN) | 105 A |
| Energía | 76.80 Wh |
| Longitud | 150.0 mm |
| Número comparativo | BTX7A-BS |
| Polo negativo | front right |
| Polo positivo | front left |
| Purga de aire | internal |

| | |
|-----------------------------|----------------------|
| Tensión | 12V |
| Versión | MTF , with acid pack |
| Ámbito de aplicación | motorcycle |