



## BS-BATTERY Battery "BTX7L / BTX7L-BS"

MTF maintenance-free

Attach the acid pack supplied after removing the adhesive strip and allow to run evenly into all cells. Leave to stand for about 1-2 hours and then press the sealing strip on firmly. Once filled, the battery is sealed and no further maintenance is necessary.

Caution Batteries from 12 V may require recharging! Never open or drill into these sealed (MTF) batteries or remove the sealing strip!

**RRP 40,97 €**

### Datos maestros

Número de artículo del proveedor:	300620
EAN	3661451001205
UVP	40,97 €
SB-Artículo	No
Marca/Proveedor	BS-BATTERY
Unidad de medida:	PIECE
Weight	2.165 kg

### Datos técnicos

Altura	130.0 mm
Anchura	70.0 mm
Artículo	Article
Atornilladura	M5
Cantidad de llenado	0.3 l
Capacidad 10 h	6.0 Ah
Capacidad 20 h	6.3 Ah
Corriente de arranque en frío CCA (EN)	100 A
Energía	76.80 Wh
Longitud	113.0 mm
Número comparativo	BTX7L-BS
Polo negativo	front left

<b>Polo positivo</b>	front right
<b>Purga de aire</b>	internal
<b>Tensión</b>	12V
<b>Versión</b>	MTF , with acid pack
<b>Ámbito de aplicación</b>	motorcycle