



tecMATE Battery charger "BatteryMATE 150-9"

charge tester and charger in one

Quick activation of new batteries - 30-minute activation charge only for new batteries filled with acid immediately before charging, such as STD wet batteries with removable caps and "dry-charged" AGM-MF batteries supplied with a special separate acid pack.

Charge detector selectable from 15A to 150A - automatically tests the starting current of the battery up to 330CCA. A 3-second test simulates the normal engine start / stop, and a 15-second test determines the health of the battery.

Motorsports specific loading algorithm - 4-stage charge saves every 12V battery. MF-mode allows for up to 16,9V for "dry charged" AGM batteries.

Temperature regulated charge - the charging voltage is adapted to the ambient temperature. (-4 mV/°C/cell over/less 68°F/20°C).

Exact voltage measurement - the charging cables are provided with integrated voltage sensor wires for the accurate measurement of voltage at the battery.

User-friendly - the 6 position combo box switch allows selection of the correct test and charging current for the connected battery. TEST and then select the maximum charging time according to the result, press the LOAD button. The program automatically completes the charge and then checks the battery.

- CHARGING CURRENT: 9A max., 1, 2, 3, 5, 7, 9 Amp-choice
- TEST CURRENT: 150A max., 15, 35, 50, 70, 100, 150 Amp-choice
- USAGE: rooms/workshop enviroment (lowest temperature: -4°F / -20°C).
- RESCUE: start with low voltage of 1V + desulfation rescue with high performance
- IDEAL FOR: STD, AGM & GEL 12V batteries from 2 - 40Ah
- INPUT: selectable 110-120VAC / 220-240VAC 50-60Hz, with main switch and exchangeable fuse
- VERSION: Ventilated industrial housing with optional wall bracket (TS-218), 6ft / 180cm power cable and 1 pair 6ft / 180cm charging cables for high current consumption with high performance battery terminal

SAFE: No risk of overcharging. Spark suppression. Safe for long-term battery maintenance. Automatic shutdown in case of short circuit or disconnected battery. 2 years guarantee

Price: 579,00 €

Datos maestros

Número de artículo del proveedor:	10184-00
EAN	99999999
UVP	689,01 €

SB-Artículo	No
Marca/Proveedor	tecMATE
Unidad de medida:	PIECE
Weight	6.955 kg

Datos técnicos

Artículo	Article
Características	overload protection , short circuit protection
Color principal	Negro
Corriente de carga/capacidad	9.0 A
Tensión	12V
Tipo de batería	AGM , MTF , standard
Versión	workshop device
Ámbito de aplicación	motorcycle , scooter

More product images

