



CONTEC Stem "Tarantula Stick"

Ø 25,4mm, 105mm stem length, 25,4mm handlebar clamp, silver

Price: 13,99 €

Uncompromising ergonomics Those who regularly use their bike, whether as a daily means of transport in the city or on bicycle tours, should not compromise on ergonomics. In addition to the saddle, the frame geometry and the handlebar, the optimal seating position is also achieved with a suitable handlebar stem. The CONTEC stem "Tarantula Stick" can be tailored to individual needs thanks to the -10° to $+60^{\circ}$ adjustment range: By loosening the side Allen locking bolt, the angle can be changed as required. This quill stem is mounted in the fork steerer tube, where its height is also continuously adjustable. Thanks to a shaft length of 180 mm, this handlebar stem is particularly suitable for larger people and all bikers who want a more upright sitting position. The "Tarantula Stick" is made of cold-forged aluminium 6061 and is therefore particularly stiff and robust. Stainless steel bolts ensure permanent corrosion resistance and additional stability. The 4-bolt faceplate is removable and allows easy and safe mounting of the handlebar. The CONTEC stem "Tarantula Stick" is available in various dimensions. The colours: Black and silver with a polished finish. Due to its great adjustability and robust quality, this product is particularly suitable for touring and city bikes. But perhaps the most important feature: It prevents wrist, neck and upper body fatigue as well as pain, thanks to the adjustable properties that can be tailored to fit individual needs.

Datos maestros

Número de artículo del proveedor:	JD-ST103AL
EAN	4250311386720
UVP	35,95 €
SB-Artículo	Sí
Fedas-Code	160222
DST-Code	2B02
Marca/Proveedor	CONTEC
Unidad de medida:	PIECE
Weight	0.466 kg

Datos técnicos

Artículo	Article
Características	teilbar , verstellbar
Color principal	Plata
Fijación del manillar	25,4mm
Longitud del vástago	180.0 mm
Longitud de tallo	105.0 mm

Sujeción del vástago	25,4mm
Versión	Schaft
Ángulo de potencia desde	-10 °
Ángulo de potencia hasta	60 °