

CONTEC Rear Hub "Core CL"

12-speed Shimano Micro Spline, mounting width 142 mm, approx. 397 g

RRP: 79,95 €

With our Core hubs, you can build a reliable and sturdy Wheel to handle all the challenges of everyday use. Their outstanding quality also makes them ideal for use on e-bikes. Made of aluminum, the Core rear hub features 32 spoke holes, a Center Lock brake rotor mount, a 12 mm Thru Axle, and is designed for a 142 mm mounting width. The steel Microspline Freewheel Body is specifically designed for durability and longevity, as are the high-quality ball bearings. The ratchet freehub system, with 27 teeth and 3 Pawls, ensures rapid interaction between the freehub and the hub body, so that your pedaling effort is quickly converted into forward motion.

Datos maestros

Número de artículo del proveedor:	CL-RTP MICROSPLINE
EAN	4251971137950
UVP	79,95 €
Fedas-Code	160452
SB-Artículo	No
Bidex-Code	204030
DST-Code	2P04
Marca/Proveedor	CONTEC
Unidad de medida:	PIECE
Weight	0.397 kg

Datos técnicos

Alojamiento de freno	disc - Center Lock
Anchura de montaje	142 mm
Artículo	Article
Catenaria	44.5 mm
Cerchio del freno	no , yes
Color principal	Negro
Cuerpo de piñón libre	Micro Spline
Diámetro de la brida	68 mm
Diámetro del agujero del radio	for 2.00 and 2.34 mm
Eje	12mm full-floating axle
Marchas	12-speed
Material cuerpo de piñón libre	steel
Material del cuerpo del buje	Aluminium
Modelo de cubo	Core CL
Montaje	rear wheel
Número de orificios para radios	32 holes
Número de trinquetes	3 pcs.
Para rueda	standard

Sistema de rueda libre	27
Tipo	cassette
Tipo de bicicleta eléctrica	ready
Tipo de radio	J-Bend
Tipo de rodamiento	ball bearing