

CONTEC Aluminium Rim "Xeta" 27,5"

25-584, 570 mm ERD (measured including spoke holes), 16.3 mm high, 25 mm inner width, 29.3 mm outer width, approx. 534 g

RRP: 39,95 €

The ideal foundation for building a tubeless-ready wheel for 27.5" (650B) bikes with 32 spokes. Thanks to its hollow-chamber construction, the Xeta Aluminium Rim, made of 6063 aluminum, is particularly lightweight and sturdy. When assembled into a complete wheel, these rims are suitable for a system weight of up to 150 kg. With an inner rim width of 25 mm, tires ranging from 42 to 62 mm in width fit on the rim. The single-eyelet nipple holes ensure additional durability of the aluminium rim by reducing friction between the Spoke Nipples and the rim and also preventing the Nipples from grinding into the rim. The Xeta rim is only suitable for wheels with disc brakes. You can find compatible tubeless Rim Tape in our CONTEC product range.

Datos maestros

Número de artículo del proveedor:	30008497
EAN	5604315353001
UVP	39,95 €
Bidex-Code	204010
Fedas-Code	160464
DST-Code	2P02
SB-Artículo	No
Marca/Proveedor	CONTEC
Unidad de medida:	PIECE
Weight	0.515 kg

Datos técnicos

Agujero del radio	easy eyelets
Alojamiento de freno	disc - 5-hole , disc - 6-hole , disc - Center Lock , drum brake , roller brake
Altura	16.0 cm
Altura de la llanta	16.3 mm
Anchura	29.3 cm
Artículo	Article
Cerchio del freno	no
Color principal	Negro
Compatibilidad frenos	disc
ETRTO	25-584
Medida de Ruedas	27,5 "
Modelo de llanta	Xeta
Número de orificios para radios	32 holes
Para rueda	yes
Peso máximo admisible del sistema	150 kg
Sistema tubeless	tubeless ready
Tipo de bicicleta eléctrica	ready
Tipo de válvula	Sclaverand (SV)

Versión	doublewall

More product images




