

CONTEC Aluminium Rim "Xeta" 28 / 29"

35-622, 604 mm ERD (measured including spoke holes), 18.15 mm high, 35 mm inner width, 39 mm outer width, approx. 674 g

RRP: 39,95 €

The ideal foundation for building a tubeless-ready wheel for 29" bikes with 32 spokes. Thanks to its hollow-chamber construction, the Xeta Max Aluminium Rim, made of 6063 aluminum, is particularly lightweight and sturdy. When assembled into a complete wheel, these rims are suitable for a system weight of up to 150 kg. With an inner rim width of 35 mm, tires ranging from 60 to 75 mm in width fit on the rim. The single-eyelet spoke holes ensure additional durability of the aluminium rim by reducing friction between the Spoke Nipples and the rim and also preventing the Nipples from grinding into the rim. The Xeta Max rim is only suitable for wheels with disc brakes. You can find compatible tubeless Rim Tape in our CONTEC product range.

Datos maestros

Número de artículo del proveedor:	30008496
EAN	5604315353049
UVP	39,95 €
Bidex-Code	204010
Fedas-Code	160464
DST-Code	2P02
SB-Artículo	No
Marca/Proveedor	CONTEC
Unidad de medida:	PIECE
Weight	0.635 kg

Datos técnicos

Agujero del radio	easy eyelets
Alojamiento de freno	disc - 5-hole , disc - 6-hole , disc - Center Lock , drum brake , roller brake
Altura	18.0 cm
Anchura	39.0 cm
Artículo	Article
Cerchio del freno	no
Color principal	Negro
Compatibilidad frenos	disc
ETRTO	35-622
Medida de Ruedas	28 / 29 "
Modelo de llanta	Xeta
Número de orificios para radios	32 holes
Para rueda	yes
Peso máximo admisible del sistema	150 kg
Sistema tubeless	tubeless ready
Tipo de bicicleta eléctrica	ready
Tipo de válvula	Sclaverand (SV)
Versión	doublewall

More product images




