

## CONTEC Aluminium Rim "Exit"

21-584, 570 mm ERD (incl. spoke holes measured), 16.2 mm high, 21.2 mm inner width, 26.3 mm outer width, approx. 503 g

**Price: 14,99 €**

A robust rims for building a classic wheel for 27.5" wheels with 32 spokes. Thanks to the hollow chamber design, the 6063 aluminum rims are particularly light and stable. In the finished Wheel, these rims are suitable for a system weight of up to 150 kg. With an inner rim width of 21 mm, tires ranging in size from 35 to 62 mm fit on the rim. The single eyeletted nipple holes ensure additional durability of the rim by reducing the friction between the Spoke Nipple and the rim and also prevent the Nipples from working their way into the rim. The Exit rim is only suitable for wheels with disc brakes.

### Datos maestros

Número de artículo del proveedor:	30002534
EAN	4251971141148
UVP	29,95 €
Bidex-Code	204010
Fedas-Code	160464
DST-Code	2P02
SB-Artículo	No
Marca/Proveedor	CONTEC
Unidad de medida:	PIECE
Weight	0.503 kg

### Datos técnicos

Agujero del radio	easy eyelets
Alojamiento de freno	disc - 5-hole , disc - 6-hole , disc - Center Lock , drum brake , roller brake
Altura	16.0 cm
Altura de la llanta	16 mm
Ancho exterior de la llanta	26 mm
Ancho interior de la llanta	21 mm
Anchura	26.3 cm
Artículo	Article
Cerchio del freno	no
Color de los ojales	silver
Color principal	Negro
Compatibilidad frenos	disc
Diámetro del agujero del radio	for 2.00 mm
ERD	570 mm
ETRTO	21-584
Forma de cámara hueca	symmetrical
Medida de Ruedas	27,5 "
Modelo de llanta	Exit
Número de orificios para radios	32 holes
Para rueda	yes

<b>Peso máximo admisible del sistema</b>	150 kg
<b>Tensión máxima de los radios</b>	1.200 Nm
<b>Texto configurador de ruedas</b>	suitable for E-bike
<b>Tipo de bicicleta eléctrica</b>	ready
<b>Tipo de válvula</b>	Sclaverand (SV)
<b>Versión</b>	doublewall