

CONTEC Aluminium Rim "Exit" 27,5"

23-584, 571 mm ERD (measured including spoke holes), 16.2 mm high, 23.2 mm inner width, 28.3 mm outer width, approx. 532 g

RRP: 29,95 €

A sturdy aluminium rim for building a classic fixed-gear wheel for 27.5" wheels with 32 spokes. Thanks to its hollow-chamber construction, this 6063 aluminum rim is particularly lightweight and sturdy. When assembled into a wheel, these rims are suitable for a system weight of up to 150 kg. With an inner rim width of 23 mm, tires ranging from 37 to 62 mm in width fit on the rim. The single-eyelet nipple holes ensure additional durability of the rim by reducing friction between the Spoke Nipples and the rim and also preventing the Nipples from grinding into the rim. The Exit rim is only suitable for wheels with disc brakes.

Datos maestros

Número de artículo del proveedor:	30002551
EAN	4251971141155
UVP	29,95 €
Bidex-Code	204010
Fedas-Code	160464
DST-Code	2P02
SB-Artículo	No
Marca/Proveedor	CONTEC
Unidad de medida:	PIECE
Weight	0.532 kg

Datos técnicos

Agujero del radio	easy eyelets
Alojamiento de freno	disc - 5-hole , disc - 6-hole , disc - Center Lock , drum brake , roller brake
Altura	16.0 cm
Altura de la llanta	16 mm
Ancho exterior de la llanta	28 mm
Ancho interior de la llanta	23 mm
Anchura	28.3 cm
Artículo	Article
Cerchio del freno	no
Color de los ojales	silver
Color principal	Negro
Compatibilidad frenos	disc
Diámetro del agujero del radio	for 2.00 mm
ERD	571 mm
ETRTO	23-584
Forma de cámara hueca	symmetrical
Medida de Ruedas	27,5 "
Modelo de llanta	Exit

Número de orificios para radios	32 holes
Para rueda	yes
Peso máximo admisible del sistema	150 kg
Tensión máxima de los radios	1.200 N
Tipo de bicicleta eléctrica	ready
Tipo de válvula	Sclaverand (SV)
Versión	doublewall

More product images




