

CONTEC Aluminium Rim "Exit" 28 / 29"

21-622, 608 mm ERD (measured including spoke holes), 16.2 mm high, 21.2 mm inner width, 26.3 mm outer width, approx. 536 g

RRP: 29,95 €

A sturdy Aluminium Rim for building a classic fixed-gear wheel for 29" wheels with 32 spokes. Thanks to its hollow-chamber construction, this 6063 aluminum rim is particularly lightweight and sturdy. When assembled into a wheel, these rims are suitable for a system weight of up to 150 kg. With an inner rim width of 21 mm, tires ranging from 35 to 62 mm in width fit on the rim. The single-eyelet nipple holes ensure additional durability of the rim by reducing friction between the Spoke Nipples and the rim and also preventing the nipples from grinding into the rim. The Exit Master Aluminium Rim is only suitable for wheels with disc brakes.

Datos maestros

Número de artículo del proveedor:	30002537
EAN	5604315265717
UVP	29,95 €
Bidex-Code	204010
Fedas-Code	160464
DST-Code	2P02
SB-Artículo	No
Marca/Proveedor	CONTEC
Unidad de medida:	PIECE
Weight	0.536 kg

Datos técnicos

Agujero del radio	easy eyelets
Alojamiento de freno	disc - 5-hole , disc - 6-hole , disc - Center Lock , drum brake , roller brake
Altura de la llanta	16 mm
Ancho exterior de la llanta	26 mm
Ancho interior de la llanta	21 mm
Artículo	Article
Cerchio del freno	no
Color de los ojales	silver
Color principal	Negro
Compatibilidad frenos	disc
Diámetro del agujero del radio	for 2.00 mm
ERD	608 mm
ETRTO	21-622
Forma de cámara hueca	symmetrical
Medida de Ruedas	28 / 29 "
Modelo de llanta	Exit
Número de orificios para radios	32 holes
Para rueda	yes

Peso máximo admisible del sistema	150 kg
Tensión máxima de los radios	1.200 N
Tipo de bicicleta eléctrica	ready
Tipo de válvula	Sclaverand (SV)
Versión	doublewall

More product images




