



## CONTEC Aluminium Rim "Exit"

21-622, 608 mm ERD (measured incl. spoke holes), 16.2 mm high, 21.2 mm inner width, 26.3 mm outer width, approx. 536 g

**Price: 14,99 €**

A robust rims for building a classic wheel for 29" wheels with 32 spokes. Thanks to the hollow chamber design, the 6063 aluminum rims are particularly light and stable. In the finished Wheel, these rims are suitable for a system weight of up to 150 kg. With an inner rim width of 21 mm, tires ranging in size from 35 to 62 mm fit on the rim. The single eyeletted nipple holes ensure additional durability of the rim by reducing the friction between the Spoke Nipple and the rim and also prevent the Nipples from working their way into the rim. The Exit Master rim is only suitable for wheels with disc brakes.

### Datos maestros

Número de artículo del proveedor:	30002537
EAN	4251971141179
UVP	29,95 €
Bidex-Code	204010
Fedas-Code	160464
DST-Code	2P02
SB-Artículo	No
Marca/Proveedor	CONTEC
Unidad de medida:	PIECE
Weight	0.536 kg

### Datos técnicos

Agujero del radio	easy eyelets
Alojamiento de freno	disc - 5-hole , disc - 6-hole , disc - Center Lock , drum brake , roller brake
Altura de la llanta	16 mm
Ancho exterior de la llanta	26 mm
Ancho interior de la llanta	21 mm
Artículo	Article
Cerchio del freno	no
Color de los ojales	silber
Color principal	Negro

<b>Compatibilidad frenos</b>	disc
<b>Diámetro del agujero del radio</b>	für 2,00 mm
<b>ERD</b>	608 mm
<b>ETRTO</b>	21-622
<b>Forma de cámara hueca</b>	symmetrical
<b>Medida de Ruedas</b>	28 / 29 "
<b>Modelo de llanta</b>	Exit
<b>Número de agujeros</b>	32 holes
<b>Para rueda</b>	yes
<b>Peso máximo admisible del sistema</b>	150 kg
<b>Tensión máxima de los radios</b>	1.200 Nm
<b>Texto configurador de ruedas</b>	suitable for E-bike
<b>Tipo de válvula</b>	Sclaverand (SV)
<b>Versión</b>	doublewall

### More product images

