



CONTEC Rear Wheel "Xeta + CONTEC Core CL "

29" Rear Wheel

RRP 139,95 €

Our Xeta Core 30 29" Boost Rear Wheel, featuring a SHIMANO Micro Spline Freewheel Body, will win you over with its exceptional durability in the face of both major and minor challenges you encounter during sporty rides or on everyday trails. With a maximum system weight capacity of up to 150 kg, our Wheel has plenty of headroom for demanding rides, heavier Fahrers, and modern E-MTBs. The aluminum Core rear hub, featuring a Centerlock brake disc mount and a 12 mm Thru Axle, boasts a proven, robust design for minimal maintenance. The freewheel body for Shimano Micro Spline is made of robust CrMo steel for exceptional durability. 32 bent 2 mm stainless steel spokes also guarantee a high load capacity and thus the longevity of this wheel. The Xeta Max aluminium rim is tubeless-ready and, with a 30 mm inner rim width, is ideally suited for high-volume tires. All CONTEC wheels are assembled by experienced specialists at our wheel manufacturing facility in Hoya, Lower Saxony (Germany), and perfectly trued for you using state-of-the-art technology.

Datos maestros

Número de artículo del proveedor:	F=3498164 N=7476223
EAN	4251971142954
UVP	139,95 €
Bidex-Code	204060
DST-Code	2P01
SB-Artículo	No
Fedas-Code	160462
Marca/Proveedor	CONTEC
Unidad de medida:	PIECE
Weight	1.2 kg

Datos técnicos

Agujero del radio	easy eyelets
Alojamiento de freno	disc - Center Lock
Altura de la llanta	18.1 mm
Anchura de montaje	148 mm
Artículo	Article
Color del buje	black
Color de llanta	black
Color de radio	black
Color principal	Negro
Compatibilidad del sistema	12-speed
Cuerpo de piñón libre	Micro Spline
Diámetro de radio	2,00 mm
ETRTO	30-622
Eje	12mm full-floating axle
Longitud del radio derecho	292 mm
Longitud del radio izquierdo	294 mm

Material de radios	stainless steel
Medida de Ruedas	28 / 29 "
Modelo de cubo	Core CL
Modelo de llanta	Xeta
Montaje	rear wheel
Número de orificios para radios	32 holes
Para rueda	yes
Peso máximo admisible del sistema	150 kg
Sistema de cambio	12-speed
Sistema de frenado	for disc brake, Center Lock
Sistema tubeless	tubeless ready
Tipo de bicicleta eléctrica	ready
Tipo de llanta	tubeless ready
Tipo de válvula	Sclaverand (SV)
Versión	doublewall
Ámbito de aplicación	MTB